



Reg. A/D

HZL/RDC/EC-CR/2022-23/H2

Date: 24.05.2023

To.

The Deputy Director (S) /Scientist -C
Ministry of Environment, Forest & Climate Change,
Integrated Regional Office, A-209&218, Aranya Bhawan,
Jhalana Institutional Area Jaipur-302004

File no: IV/ENV/R/IND-115/758/2009

Sub: Six Monthly Environmental compliance report for the Integrated Project at Dariba, HZL (Zinc Smelter (5,00,000 TPA), Lead Smelter (1,25,000 TPA), Captive Power Plant (255 MW) and expansion of Rajpura Dariba Mine (9,00,000 to 1,08,000 TPA) along with Beneficiation Plant (9,00,000 to 12,00,000 TPA) at Village Dariba, Tehsil-Railmagra, Dis. Rajsamand from October'22 to March'23.

Ref:

- 1. EC Letter No. J-11011/380/2008-IA II (I) dated 4.11.2009
- Amendment in EC No. J-11011/380/2008-IA II (1) dated 20.12.2011.
- Expansion EC Letter No. J-11015/380/2008-IA II (I) dated 26.7.2018 (RD Mine 0.9 MTPA to 1.08 MTPA)

Sir,

With reference to aforesaid subject and cited references, it is to inform that we are herewith submitting six monthly Compliance report for the conditions stipulated in the Environment Clearances of Integrated Project at Dariba, HZL (Zinc Smelter (5,00,000 TPA), Lead Smelter (1,25,000 TPA), Captive Power Plant (255 MW) and expansion of Rajpura Dariba Mine (9,00,000 to 1,08,000 TPA) along with Beneficiation Plant (9,00,000 to 12,00,000 TPA) for the period from October'22 to March'23 along with monitoring data report for your kind consideration.

The copy of above compliance report is also being sent in soft format through email
to (rocz.lko-met@gov.in; m_env@rediffmail.com) for your kind perusal. Also copy
of Dariba Smelting complex EC Compliance has been uploaded on company
website https://www.hzlindia.com/sustainability/environment-compliance/



We trust that the measures taken towards environmental safeguards comply with the stipulated environmental conditions. We look forward to your further guidance which shall certainly help us in our endeavor to further improve our Environmental Management Practices.

Hope the above is in line with statutory requirements.

Thanking you,

For Hindustan Zinc Limited

rendel.

Yours faithfully,

(Rajendra Agrawal)

Head Smelter

Dariba Smelter Complex

Enclosures: Six monthly EC compliance report with Annexure:

	1440	
Annexure I	1	Stack Monitoring Report
Annexure II	3	Average Ambient Air Quality Monitoring Results (RDM)
Annexure III	+	Ambient Air Quality Monitoring Results (DSC)
Annexure IV	ž.	Ambient Air Quality Monitoring Report (Outside Plant)
Annexure V	į.	Continuous Ambient Air Quality Monitoring Results
Annexure VI	į į	Work Zone Environment Monitoring Results
Annexure VII	18	Fugitive Emission Monitoring Results
Annexure VIII	1	Treated Effluent (ETP Outlet) Quality Report
Annexure IX	340	Average Ground Water Monitoring Results (Around Tailing Dam Area
Annexure X	ġ.	Average Surface & Ground Water Monitoring Results (Around RD Mine & Tailing Dam Area)
Annexure XI	12	Ambient Noise Monitoring Report
Annexure XII	:	Average Sulphur and ash content in coal
Annexure XIII	ig.	Expenditures made in Environmental control measure
Annexure XIV	i	Funds earmarked towards Environmental control measure
Ce:		

Cc:

- The Member Secretary, Rajasthan State Pollution Control Board, 4th Institutional Area, Jhalana Doongari, Jaipur-302004
- In-charge (Zonal officer)
 Central Pollution Control Board
 Vithal Market, Paryavaran Parisar, E-5, Arera Colony, Bhopal, – 462 016 (MP)
- Group Incharge (Mines)
 Rajasthan State Pollution Control Board,
 4th, Institutional Area, Jhalana Doongari, Jaipur-302004
- The Regional office Rajasthan State Pollution Control Board, Old Excise building, Kalalwati, Rajnagar Rajsamand- 313324
- Office Copy



Six Monthly Compliance Report to Environmental Clearance Conditions of



Dariba Integrated Project,
M/s Hindustan Zinc Limited,
Dariba – 313 211, Rajsamand,
Rajasthan

For the period: October-2022 to March-2023

(1. EC Letter No. J-11011/380/2008-IA II (I) dated 4.11.2009;

- 2. Amendment in EC No. J-11011/380/2008-IA II (I) dated 20.12.2011;
- 3. Expansion EC Letter No. J-11015/380/2008-IA II (I) dated 26.7.2018 (RD Mine 0.9 MTPA to 1.08 MTPA)



Introduction:

S. No	Particulars	Details
1	Name of Project	 M/s Hindustan Zinc Limited, Dariba Integrated Project
2	Address of Project	 M/s Hindustan Zinc Limited, Dariba Integrated Project, Village Dariba, Tehsil- Railmagra, District- Rajsamand, Rajasthan, 313211
3	Environment Clearance Letter	 EC Letter No. J-11011/380/2008-IA II (I) dated 4.11.2009; Amendment in EC No. J-11011/380/2008-IA II (I) dated 20.12.2011;
	no & Date	 Expansion EC Letter No. J-11015/380/2008-IA II (I) dated 26.7.2018 (RD Mine 0.9 MTPA to 1.08 MTPA)
4	Regional Office	• IV/ENV/R/Ind-115/758/2009
#	File No.	• IV/ENV/R/Ind-115/994/2019
5	Status of Project	Operational

Rajpura Dariba Complex of Hindustan Zinc Limited, located in Railmagra Tehsil of District Rajsamand in Rajasthan, includes Rajpura Lead Zinc Dariba Mine and Dariba Lead Zinc Smelter Complex. Rajpura Dariba deposit extends over a lease area of 1142.21 ha with estimated in-situ ore Resources & Reserves stands at 60 million tons approx. Rajpura Dariba Mine consists of mining of Lead-Zinc ore and its beneficiation to produce Lead & Zinc Concentrate which are being sent to Smelters where metals are extracted. Dariba Smelter Complex is Zinc and Lead Smelting complex consisting of two different smelting streams viz., hydrometallurgical (Roast-Leach Electrowinning) Zinc Smelter and Lead Smelter based on Pyro-route for smelting & electro refining. The power requirements of the plants are met through 170 MW (2x85MW) coal based captive power plants.

S. No.	Unit	Capacity	Year of Commissioning	Production in FY 2022-23
1	Lead & Zinc Ore mining	1.08 Million MT	1983	1740463 MT
2	Lead & Zinc Ore Beneficiation	1.2 Million MT	1983	940219 MT
3	Zinc Smelter	Zn: 2,50,000 MT	March 2010	250000 MT
4	Lead Smelter	Pb: 1,25,000 MT	July 2011	112715 MT
5	CPP	CPP; 170 MW	Unit 1- Feb 10 Unit 2- June 10	Unit 1- 490 MU Unit 2- 453 MU

Details of Consents to Operate & Hazardous Waste Authorization (HWA) granted to units are given below:



Unit Name	CTO/HWA Ref. No.	Status	Application No. & Date
	CTO Details		
Lead & Zinc Ore mining	F(Mines)/Rajsamand(Railmagra)/1724(1)/2018- 2019/7163-7167 dated 28.02.2023	Valid till 29/2/2028	
Lead & Zinc Ore Beneficiation	F(Mines)/Rajsamand(Railmagra)/6460(1)/2019- 20/6027-6030 dated 18.3.2020	Valid till 28/2/2023	Applied for renewal on 22/10/2022 via application I.D. 323229
Zinc Smelter	F(HDF)/Rajsamand(Railmagra)/6461(1)/2020- 2021/4691-4693	Valid till 31/10/2023	
Lead Smelter	F(HDF)/Rajsamand(Railmagra)/6461(1)/2020- 2021/4945-4947	Valid till 31/08/2024	
CPP	F(HDF)/Rajsamand(Railmagra)/6461(1)/2020- 2021/5140-5142	Valid till 31/10/2023	
	HWA Details		
Dariba Smelter Complex	F(HSW)/Rajsamand(Railmagra)/3(1)/2015- 2016/5475-5477	Valid till 31/03/2025	
RD Mine & Beneficiation Plant	F(HSW)/Rajsamand(Railmagra)/5(1)/2016- 2017/4038-4040 dated 18.11.2021	Valid till 17.11.2026	



COMPLIANCE STATUS

- Environment Clearance Letter No. J-11011/380/2008-IA II (I) dated 4.11.2009
- Amendment in EC No. J-11011/380/2008-IA II (I) dated 20.12.2011.
- Expansion EC Letter No. J-11015/380/2008-IA II (I) dated 26.7.2018 (RD Mine 0.9 MTPA to 1.08 MTPA)
- Period of Compliance: October 2022 to March 2023

A.	EC Specific Conditions	Status of Compliance
i)	No construction work related to expansion at the proposed project site shall be started without obtaining prior clearances / approvals for the linked mining component from the Indian Bureau of Mines (IBM) and State Govt. of Rajasthan. A copy of the mining lease approval from the Indian Bureau of Mines (IBM) and State Govt. of Rajasthan shall be submitted to the Ministry and its Regional Office at Lucknow before initiating any construction work at site related to mining.	 Noted for compliance Project is under operational stage and as of now no construction work related to expansion is under progress.
ii)	The project proponent shall obtain 'Consent to Establish' and 'Consent to Operate' from the Rajasthan State Pollution Control Board (RSPCB) and effectively implement all the conditions stipulated therein.	 Complied, 'Consent to Establish' and 'Consent to operate' have been obtained from the Rajasthan State Pollution Control Board (RSPCB) vide letter no. F(Tech)/Rajsamand (Railmagra)/2/1/2009- 2010/3666 dated 12/11/2009 and all the conditions stipulated therein are being implemented.
iii)	The environmental clearance is subject to approval of the State Land use Department, Government of Rajasthan for diversion of agricultural land for non-agricultural use.	 Complied, Approval of the State Land Use department, GoR was already obtained and submitted to RO, MOEF&CC with Six monthly compliance report. Letter Attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.



VI)

High

Six Monthly EC Compliance Report (October 2022- March 2023, Hindustan Zinc Limited, Dariba Integrated Project, Village Dariba, Tehsil - Railmagra, Dist. - Rajsamand, Rajasthan

- iv) The project proponent shall develop fodder plots in the non-mineralized area in lieu of use of grazing land. Monitoring of land use pattern shall be carried out once in three years by digital processing of the area using multi-data computer compatible tape.
- Complied, the monitoring of land use using satellite imagery was done for the Mine Lease Area in August 2018. Final report is submitted along with reply letter vide. HZL/DSC/ENV/ EC/2018/01 Date: 04.12.2018. Report enclosed in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022. Satellite imagery LULC is to be carried out once in 5 years.
- v) The gaseous emissions from various process units shall confirm to the standards prescribed by the concerned authorities from time to time. The State Board may specify more stringent standards for the relevant parameters keeping in view the nature of the industry and its size and location. At no time the emissions level shall go beyond the prescribed standards. In the event of failure of any pollution control system adopted by the unit, the respective unit should not be restarted until the control measures are rectified to achieve the desired efficiency.

efficiency

Complied.

- Various mechanisms adopted for controlling of all gaseous emissions coming from the plants.
- Gaseous Emissions Monitoring is being done on a regular basis and results are well within standards prescribed by the concerned authorities. The same is also evidenced from the various third-party (NABET Approved) analytical reports which are enclosed as Annexure No. I

precipitators (ESPs) of not less than 99.87 % efficiency shall be provided to captive power plant to limit particulate matter within 50 mg/Nm3. The height of the stacks shall be as per the standards prescribed under Environment (Protection) Act, 1986. Low NOx burners shall be provided to control NOx emissions. NOx emissions shall be restricted to 750 mg/Nm3 by using low NOx burners. On-line stack emission monitoring equipments for continuous monitoring of SO2, NOx, SPM and O2 shall be provided to the stacks of captive power plant and sulphuric acid plant and all the pollution control measures shall be inter-locked. The company shall install

fume extractors and bag filters to

control the emissions from all melting

and casting units. Off gas from the

Complied.


electrostatic

- High Efficiency ESPs, (99.95%) provided to Captive Power Plant (CPP) are designed for particulate matter concentration less than 50 mg/Nm3 at outlet.
- The height of the stacks is as per the standards prescribed under the Environment (Protection) Act, 1986. The height of the Acid Plant, CPP and TGT plant stack is 100 m, 165 m, and 105 m respectively.
- Continuous on-line stack emission monitoring equipment for SO2, NOx and SPM has been provided to the stack of captive power plant and for SO2 to the Sulphuric acid plants respectively in Zinc and Lead Smelter
- Off gas from the Sulphuric acid plant, blast and fuming furnace plant, copper recovery plant of lead plant are treated in the calcine based scrubbing plant where the SO2 is




Sulphuric acid plant, blast and fuming furnace plant, copper recovery plant shall be treated in the calcine based scrubbing plant where the SO2 shall be removed before letting out to the atmosphere. Adequate stack height shall be provided for proper dispersion of pollutants like SO2, NOx etc.

- recovered before letting out to the atmosphere.
- Opacity meters have been installed for continuous monitoring of particulate matter (PM) at stack of CPP, Zinc dust and Zinc dross Stack.
- Adequate numbers of air pollution control devices have been installed at all the material transfer points & silos.
- Calibration of all instruments are being done on regular basis.
- Photographs of ESP, Stacks, CEMS, CAQQMS, display at main gate, Sampling port are enclosed.





Acid Plant Hot ESP



SKS Plant Hot ESP




CAAQMs




Display at Main Gate






Port hole in stack



CPP Stack



8 Field ESP with 165 mt Stack height



SO2

Existing Analyzer



SO2 ppm Reading in HMI

Online Server Reading

- vii) As reflected in the EIA/EMP, Double Conversion Double Adsorption (DCDA) plant for Sulphuric acid recovery from SO2 shall be provided. The company shall ensure that SO2 emissions from the Zinc and lead smelter plant are taken to existing
- Complied.
- Double Conversion Double Adsorption (DCDA) plant for Sulphuric acid recovery from SO2 has been provided.
- SO2 emissions from the Zinc and Lead Plant Smelter are taken to respective Sulphuric




Sulphuric acid plant properly and converted to Sulphuric acid. The stack from the Sulphuric acid plant shall be provided with on-line stack emission monitoring equipment for continuous monitoring of SO2.

- acid plant properly and converted to Sulphuric acid,
- The stack from the Sulphuric acid plant provided with on-line stack emission monitoring equipment for continuous monitoring of SO2.



DCDA Gas Conditioning Plant (GCP) with 100 mt Stack Height



- viii) SO2 emissions shall be controlled less than 1.5 kg/ton of Sulphuric acid (H2SO4) produced. Acid mist emissions from the stack shall conform to the statutory limit of 50 mg/Nm3 by providing candle filter system and reports submitted to the Ministry including its Regional Office at Lucknow, CPCB and RSPCB.
- Complied, SO2 Emission levels are well within the prescribed limit.
- SO2 Emission level from stack are maintained below 1.5 kg/Ton of 100 percent concentrated acid produced from acid plant. Table is incorporated in the point below.

Months	Acid Plant (Zn Smelter) Roaster-1	Acid Plant (Zn Smelter) Roaster-2	TGT Stack (Pb Stack)
	SO ₂ (K	g/T of H ₂ SO ₄	Production)



Oct'22	0.80	1.09	0.22
Nov'22	0.81	1.03	0.29
Dec'22	0.85	1.10	0.32
Jan'23	0.86	1.04	0.11
Feb'23	0.79	1.03	0.11
Mar'23	0.73	0.99	0.12

 All Monitoring Reports are enclosed as Annexure I

ix) The critical parameters such as SPM, RSPM, NOx, SO2 and acid mist in the ambient air within the impact zone, peak particle velocity at 300 m distance or within the nearest habitation, whichever is closer shall be monitored periodically. Further, quality discharged water shall also monitored [(TDS, DO, pH and Total Suspended Solids (TSS)]. monitored data shall be uploaded on the website of the company as well as displayed on a display board at the project site at a suitable location near the main gate of the Company in public domain. Analysis reports for the ambient, stack and fugitive emission shall be submitted to the Ministry's Regional Office at Lucknow, CPCB

and RSPCB.

Complied

- Third Party Periodical monitoring of various parameters i.e. PM10, PM2.5, NOx and SO2 is being done in the ambient air within the impact zone.
- Four nos. of Continuous Ambient Air Quality Monitoring Stations (CAAQMS) have been established
- Third party monitoring of Ambient air quality carried out by M/s Eko Pro Engineers, which is NABL and MoEF&CC accredited laboratory.

	Observed Value				
Parameters (μg/ m3)	Near Main Gate	Near Storm Water Pond	Near CPP Area	Near SLF Area	
PM10	82.44	78.84	78.30	82,40	
PM2.5	44.70	40.19	39.71	40.33	
SO2	15.65	16.78	14.79	15.14	
NO2	27.78	31.52	26.48	26.43	
CO	0.95	0.90	0.88	0.87	
Pb	< 0.1	< 0.1	< 0.1	<0.1	
Ni	<15	<15	<15	<15	
As	<5	<5	<5	<5	

- Average Ambient Air Quality Monitoring results for mine are enclosed herewith as Annexure II and for DSC as Annexure III.
- Eight nos. of AAQMS have been established at buffer zone for ambient air quality monitoring are enclosed as Annexure IV.
- Zero liquid discharge is being maintained by ETP of capacity of 9000 KLD, RO of 8850 KLD and MEE of 600 KLD capacity.
- The monitored data has been displayed on display



		•	board at website Compliar https://wwent-comp Six Moralong wistack and submitted Lucknow	along hee report of the second	with S port. I ndia.co. Environ Analysi e emiss	ix Mor Link of m/susta ment of s reportsion are ional of	of the inability Compliants for the enclose	report y/environ ance re the amb	ment t is onm eport pient, peing
x)	Ash content in the coal shall not exceed 35 %. Sulphur content in coal shall be restricted to 1.5% to contain SO2 emissions.		Complied being ar within th Monitori	nalyzed e limit (on re	gular b and 1.5	asis ar % respe	nd are ectively	well
xi)	The company shall install continuous air quality monitoring stations. Data monitored shall be submitted to the Ministry and CPCB/SPCB once in six		Four no Monitori installed	ing St		(CAA	QMS)	Air Ç have	uality beer
		Locati			e Months				
	The state of the s	Locati	Parame			Mo	nths		
	months.	Locati	ters	Oct'22	Nov'22			Feb'23	Mar'
	The state of the s		A 200 A	Oct'22 71,05	Nov'22 71.98	Dec'22 74.51	Jan*23 67.25	64.71	67.5
	The state of the s	Near to	ters (μg/m3) PM SO2	71,05 35.78	71.98 35.12	Dec'22 74.51 34.64	Jan'23 67,25 14.87	64.71 5.96	67.5 9.12
	The state of the s	Near to Main	ters (μg/m3) PM	71,05	71.98	Dec'22 74.51	Jan*23 67.25	64.71	- Contraction
	The state of the s	Near to	ters (μg/m3) PM SO2	71,05 35.78	71.98 35.12 34.4 0.53	74.51 34.64 34.83 0.59	Jan'23 67,25 14.87 10.50 0.80	64.71 5.96 9.80 1.02	67.5 9.12 14.3 0.81
	The state of the s	Near to Main Gate (South	ters (µg/m3) PM SO2 NOX CO PM	71,05 35.78 36.37 0.43	71.98 35.12 34.4 0.53 74.91	74.51 34.64 34.83 0.59 75.03	Jan'23 67.25 14.87 10.50 0.80 46.79	64.71 5.96 9.80 1.02 46.42	67.5 9.12 14.3 0.81 47.2
	The state of the s	Near to Main Gate (South West) Near to	ters (µg/m3) PM SO2 NOX CO PM SO2	71,05 35,78 36,37 0,43 74,75 36,02	71.98 35.12 34.4 0.53 74.91 34.9	74.51 34.64 34.83 0.59 75.03 34.84	Jan'23 67,25 14.87 10.50 0.80 46.79 12.42	64.71 5.96 9.80 1.02 46.42 12.28	67.5 9.12 14.3 0.81 47.2 5.43
	The state of the s	Near to Main Gate (South West) Near to SWP	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX	71,05 35.78 36.37 0.43 74.75 36.02 35.61	71.98 35.12 34.4 0.53 74.91 34.9 34.52	74.51 34.64 34.83 0.59 75.03 34.84 35.20	Jan*23 67,25 14.87 10.50 0.80 46.79 12.42 8.57	64.71 5.96 9.80 1.02 46.42 12.28 11.94	67.5 9.12 14.3 0.81 47.2 5.43 9.12
	The state of the s	Near to Main Gate (South West) Near to SWP (North West)	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO	71,05 35,78 36,37 0,43 74,75 36,02 35,61 0,50	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05	Jan'23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06	67.5 9.12 14.3 0.81 47.2 5.43 9.12 0.54
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 PM PM	71.05 35.78 36.37 0.43 74.75 36.02 35.61 0.50 75.65	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86	Jan'23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43	67.5 9.12 14.3 0.81 47.2 5.43 9.12 0.54
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2	71,05 35.78 36.37 0.43 74.75 36.02 35.61 0.50 75.65 37.22	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02	Jan*23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22	67.5 9.12 14.3 0.81 47.3 5.4; 9.1; 0.54 56
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to CPP	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX	71,05 35,78 36,37 0,43 74,75 36,02 35,61 0,50 75,65 37,22 34,97	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02 36.9	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02 31.88	Jan'23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74 29.19	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22 29.98	67.5 9.12 14.3 0.81 47.2 5.42 9.12 0.54 5.6 5.00 41
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO	71,05 35.78 36.37 0.43 74,75 36.02 35.61 0.50 75.65 37.22 34.97 0.61	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02 36.9 1.03	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02 31.88 0.92	Jan*23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74 29.19	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22 29.98 1.34	67.5 9.12 14.3 0.81 47.3 5.4; 9.1; 0.54 56. 5.0; 41.
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to CPP (North East)	ters (µg/m3) PM SO2 NOX CO PM	71,05 35,78 36,37 0,43 74,75 36,02 35,61 0,50 75,65 37,22 34,97 0,61 80,18	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02 36.9 1.03 75.95	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02 31.88 0.92 79.61	Jan'23 67.25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74 29.19 1.14 70.77	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22 29.98 1.34 75.39	67.5 9.12 14.3 0.8 47.3 5.4 9.1, 0.5 56. 5.0 41. 0.8
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to CPP (North East)	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX	71,05 35,78 36,37 0,43 74,75 36,02 35,61 0,50 75,65 37,22 34,97 0,61 80,18 29,7	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02 36.9 1.03 75.95 17.27	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02 31.88 0.92 79.61 26.11	Jan'23 67,25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74 29.19 1.14 70.77 12.25	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22 29.98 1.34 75.39 13.74	67.5 9.12 14.2 0.8 47.2 5.4, 9.1, 0.5 56, 5.0 41, 0.8 60, 10,
	The state of the s	Near to Main Gate (South West) Near to SWP (North West) Near to CPP (North East)	ters (µg/m3) PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX CO PM SO2 NOX	71,05 35,78 36,37 0,43 74,75 36,02 35,61 0,50 75,65 37,22 34,97 0,61 80,18	71.98 35.12 34.4 0.53 74.91 34.9 34.52 0.97 77.77 35.02 36.9 1.03 75.95	74.51 34.64 34.83 0.59 75.03 34.84 35.20 1.05 71.86 28.02 31.88 0.92 79.61	Jan'23 67.25 14.87 10.50 0.80 46.79 12.42 8.57 0.93 55.29 9.74 29.19 1.14 70.77	64.71 5.96 9.80 1.02 46.42 12.28 11.94 1.06 63.43 13.22 29.98 1.34 75.39	67.5 9.12 14.3 0.8 47.3 5.4 9.1 0.5 56. 5.0 41.

and being submitted to the Regional Office.

MOEF&CC Lucknow, CPCB and RSPCB.



xii)

Fugitive dust emissions in the Zinc, Lead and Copper concentrate handling area and at various transfer points shall be minimized by provision of dust suppression system. The trucks carrying concentrate shall be fully covered. The Company shall improve overall housekeeping by asphalting the internal roads and to reduce the generation of fugitive dust from vehicle movements.

Complied.

- Fugitive dust emissions in the Zinc and Lead concentrate handling area and at various transfer points is mitigated by provision of dust suppression system and bag filters.
- Water Sprinkling System already installed in the Raw Material Handling of the Zinc Plant, Captive Power Plant and Lead Plant.
- Mechanized road sweepers are deployed for regular cleaning on the roads to reduce fugitive dust from vehicle movement.
- The trucks carrying concentrate are covered with tarpaulin before dispatched to Smelter from Mines.
- All roads in the plant and up to the connection to public road are concreted or black topped.



Water Sprinkling on road



Mechanized Road sweeper



Water Sprinkling System



Dust Suppression System

Fugitive emissions, acid mist vapours, fumes and SO2 shall be controlled and work environment monitored for prevailing contaminants regularly. Bag filters shall be provided to calcine handling plant, zinc dust plant, melting


Complied.

- To minimize fugitive emissions, 8-10% moisture is provided in the Zn & Pb Concentrate coming from the mines.
- Bag Filters have been provided to calcine handling



plant, dross milling plant, each coal transfer point, crushers and fly ash silos to control dust emissions. Bag filters shall be provided in fume extraction and melting and casting operations of smelter. SPM emissions from crusher house in beneficiation plant shall be controlled. Covered coal conveyors with system sprinkling water wastewater to avoid dust emissions. Coal storage area shall be provided with water sprinkling system to arrest dust. Dust extraction system shall be provided to mineral handling area, loading and unloading areas including all the transfer points. Black top paved roads shall be made within the mine boundary. The trucks carrying concentrate shall be fully covered. Asphalting/concreting of roads and water spray all around the critical areas prone to air pollution and having high levels of SPM and RPM shall be ensured.

- system, zinc dust plant, coal transfer points, crusher and fly ash silos to control dust emissions.
- Details of the bag filters have been provided along with six monthly compliance report vide letter no. HZL/DSC/Env/2011/2/2 dated 23.11.2011 and again attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.
- Covered Coal Conveyors with water sprinkling system have been installed at CPP to avoid dust emissions. Coal storage area is provided with water sprinkling system to arrest dust.
- All Internal roads and up to the public road are concreted/asphalted to reduce the dust emission.
 The trucks carrying concentrate are covered with tarpaulin and water is sprayed regularly on roads.
- Average Work Zone Environment Monitoring Results are furnished herewith as Annexure VI.
- SPM emissions from crusher house in beneficiation plant are controlled by the wet scrubbing system.
- Dust extraction system provided to mineral handling area, loading and unloading areas including all the mineral transfer points.





Bag Filter Silo



Bag filter, Cyclone at Coal Crusher



		Dust Extraction system	Tarpaulin Covered truck
xiv)	The project proponent shall carry out conditioning of the ore with water to mitigate fugitive dust emission, without affecting flow of ore in the ore processing and handling areas. Water sprinkling shall be done to minimize the dust during transportation.	 Ore conditioning is carry 10% moisture as a mitig fugitive dust. Regular water sprinkling points and at discharge carrying the crushed ore 	ative measure against ng on fine ore stock points of conveyors
xv)	Secondary fugitive emissions (particularly below 5 micron) from all the sources including Roaster plant shall	Complied, Fugitive e results is furnished he VII.	
	be controlled, regularly monitored along with ambient dust in dry day and still air condition on 24 hour basis and data submitted to the Regional Office of the Ministry at Lucknow, RSPCB and	Laurtions	Parameters (µg/ m3)
		Locations	TSPM
		Raw Material Handling (RMH)- Zinc Plant	475.31
	CPCB. It shall be ensured that the	Roaster Plant	430.35
	ambient air quality parameters conform	Calcine Handling	444.95
	to the norms prescribed by the Central	Coal Handling Plant (CPP)	417.89
	Pollution Control Board in this regard.	Fly Ash Handling	440.72
		Raw Material Handling- Lead Plant	481.68
		Near SKS Primary	419.01
sxvi)	Vehicular emissions shall be kept under control and regularly monitored. Measures shall be taken for maintenance of vehicles used in mining operation and in transportation of mineral. The vehicles carrying the mineral shall be covered with a tarpaulin and shall not be overloaded.	Mining equipment's ar are kept under control is maintenance and condit in-house workshop. During transportation of are covered with tarpaul.	by regular preventive ion monitoring at the of minerals, vehicles
xvii)	Total water requirement for the proposed smelter complex including the mining and beneficiation plants from Matrikundia dam, Gosunda dam and	Closed circuit cooling towers has been provide plant. Cooling tower by blow down from CPP	led to captive power low down and boiler



Mansiwakal dam shall not exceed 42,050 m 3 /day as per the agreements signed with Govt, of Rajasthan. As proposed, water requirement shall not exceed 184 liter/ton of Sulphuric acid produced. No ground water shall be used. Closed circuit cooling system with cooling towers shall be provided to captive power plant. All the effluent generated from gas cleaning plant, sulphuric acid plant, anode and cathode washing, lead smelter, DM plant, cooling towers and power plant shall be neutralized and metallic elements present shall be precipitated and removed. Effluents from the proposed smelters, acid plant and other associated services shall be treated in effluent treatment plant (ETP). Zinc sulphate solution from the scrubbing process shall be treated in the leaching section of the Zinc smelter. Cooling tower blow down and boiler blow down from CPP shall be neutralized and reused in dust suppression, green belt development etc. The treated effluent shall confirm to the prescribed standards and recycled in the process i.e. in gas cleaning plant, preparation of lime milk. suppression and green belt development. The effluents from sulphuric acid plant, scrubber, and general floor washings of electro-refinery plant shall also be sent to ETP for further treatment followed by two-stage Reverse Osmosis (RO) Plant. Sewage shall be treated in septic tank followed by soak pit. The rejects from the RO plant shall be evaporated in a solar evaporation pond to be constructed within smelter premises. 'Zero' discharge shall be maintained and no effluent shall be discharged outside the premises. Sewage generated shall be treated in septic tank followed by soak pit.

- ETP and recycled water again used in process.
- Effluents generated from the smelter, acid plant and other associated services are treated in Effluent Treatment Plant (ETP) followed by two-stage Reverse Osmosis (RO) Plant and Multiple Effect Evaporator (MEE). The treated effluents conform to the prescribed standards and recycle in the process. Domestic Sewage is treated in STP and recycled water used in green belt development and process.
- Third party analysis of the treated effluent is being conducted by third party which is NABL and MOEF&CC accredited laboratory.
- The values of all parameters are well within limit of prescribed standard. Analysis reports are enclosed herewith as Annexure VIII.

Parameters (in mg/L)	ETP Outlet
pH	6.87
TSS	20.90
Oil & Grease	<4.00
COD	52.80
BOD (3 days at 270C)	11.85
Sulphide (as S)	<1.00
Chloride (as cl)	295.02
Sulphates (as SO4)	162.80
Fluoride (as F)	1.06
Copper (as Cu)	0.02
Zinc (as Zn)	0.53
Cadmium (as Cd)	< 0.001
Chromium (as Cr+6)	< 0.05
Chromium (total)	< 0.005
Lead (as Pb)	0.02
Cyanide (as CN)	Absent
Nickel (as Ni)	< 0.005
Iron (as Fe)	0.32
Phosphate (as P)	0.50
Free available chlorine	< 0.2

xviii) The mine seepage water shall be collected in underground sumps and

Complied



	reused/recycled in mining and beneficiation process to minimize the fresh water consumption. Decanted water from the tailings dam shall be recycled in the beneficiation plant to ensure 'zero' discharge. Tailings from beneficiation plant after recovery of Lead and Zinc concentrates shall be sent to tailing thickener for dewatering. Water recovered from tailing thickener shall be recycled to beneficiation plant for use in the process. Tailing thickener underflow shall be partly used as backfill for mines and remaining part shall be disposed to tailing dam. Water in the tailing dam shall be allowed to settle out and pumped to the water reservoir for reuse in the process.	 Underground water from the mine is pumped to beneficiation plant for reuse and tailing dam water is also recycled to beneficiation plant for reuse. Zero discharge is being maintained.
xix)	Acid mine water, if any, has to be treated and use in plantation and existing mining activity after conforming to the standard prescribed by the competent authority.	 Not applicable as, no acid mine water is generated from mining activity.
xx)	Sewage treatment plant shall be installed for the colony. ETP shall also be provided for the mine workshop for the wastewater generated.	 Sewage treatment plant of 500 KLD and 400 KLD capacity are installed for the colony and the treated water is being used for horticulture purpose. Wastewater from the workshop is collected in the settling pit after passing through oil and grease trap system and water is regularly recycled.
xxi)	The effluent from the ore beneficiation plant shall be treated to conform to the prescribed standards and the tailings slurry shall be transported through a closed pipeline to the tailing dam. The decanted water from the tailing dam shall be re-circulated and there shall be 'zero' discharge from the tailing dam. Acid mine water, if any, shall be neutralized and reused within the plant.	 The tailing slurry is pumped through pipeline to tailing dam and decanted water is pumped back to beneficiation plant for reuse in the process. Zero discharge is maintained. No acid mine water is generated through mines.



		Taling dam pipeline
xxii)	Detailed hydrological study shall be carried out and implementation of recommendations of the detailed hydrological study shall be ensured.	 Detailed hydrological and hydro-geological study has been carried out by M/s Hydro-Geosurvey Consultants Private Limited, Jodhpur and the recommendations have been implemented. Report is attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.
xxiii)	The project proponent shall ensure that no natural water course and/or water resources shall be obstructed due to any mining operations.	 Complied, Due to underground mining activity no water course has been obstructed.
xxiv)	The project authority shall implement suitable conservation measures to augment ground water resources in the area in consultation with the Regional Director, Central Ground Water Board.	 Suitable rainwater harvesting structures have been constructed to harvest rainwater and recharge the ground water in CPP, residential colonies, schools & in mines premises. Copy of the compliance report submitted to CGWA has been submitted along with six monthly compliance reports vide letter no. HZL/DSC/Env/2011/2/2 dated 23.11.2011. Report is again in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.
xxv)	Regular monitoring of ground water level and quality shall be carried out in	Complied, Six no's of Piezometer have been installed for monitoring of ground water level and



and around the project area (mine lease, beneficiation plant and tailing dam) by establishing a network of existing wells and installing new piezometers during the operation. The periodic monitoring [(at least four times in a year- premonsoon (April-May), monsoon (August), post-monsoon (November) and winter (January); once in each season)l shall be carried out in consultation with the State Ground Water Board/Central Ground Water Authority and the data thus collected may be sent regularly to the Ministry of Environment and Forests and its Regional Office Lucknow, the Central Ground Water Authority and the Regional Director, Central Ground Water Board. If at any stage, it is observed that the groundwater table is getting depleted due to the mining activity; necessary corrective measures shall be carried out.

- quality around the tailing dam and monthly monitoring is being carried out.
- Average Ground Water Monitoring Results for October 22 to March 23 are furnished herewith as Annexure IX.

Parameters	PWI	PW2	PW3	PW4	PW5	PW6
		All f	gures in p	pm excep	t pH	
pH	7.32	7.53	7.48	7.47	7.52	7.73
Suspended Solids	17.5	25.5	14.5	19.5	23.0	12.0
Lead	BDL	BDL	BDL	BDL	BDL	BDL
Zinc	0.04	0.07	0.065	0.08	0.065	0.165
Copper	BDL	BDL	BDL	BDL	BDL	BDL
Iron	0.095	0.11	0.075	0.08	0.1	0.08
Cadmium	BDL	BDL	BDL	BDL	BDL	BDL
Nickel	0.02	0.02	BDL	BDL	BDL	BDL
Cobalt	BDL	0.01	BDL	BDL	BDL	BDL
Depth of well from surface (ft.)	145	145	150	140	145	150
Water level in, well from surface (ft.)	2.42	3.24	5.01	6.34	1.48	19.6

xxvi)

Groundwater and surface water in and around the mine shall be regularly monitored at strategic locations for heavy metals such as Ni, Co, Cu, Pb, Zn and Cd. Data should be reviewed and analyzed time to time to detect changes in the quality of ground water and surface water, if any. The monitoring stations shall be established in consultation with the Regional Director, Central Ground Water Board and the Rajasthan Pollution Control Board.

- Complied, Ground water and surface water monitoring is being carried out on monthly basis for analysis of heavy metals.
- Average Surface & Ground Water Monitoring Results (around RD Mine & Tailing Dam Area) for October 22 to March 23 is furnished herewith as Annexure X.

Parameters	Mine Water	Tailing Dam	Garland Drain	Sumer Singh Well	Nahar Singh Well
	All figu	ires în ppm ex	cept pH		
pH	7.14	7.22	7.34	7.71	7.45
Suspended Solids	25.00	26.33	27.33	6.50	10.17
Lead	BDL	BDL	BDL	BDL	BDL
Zinc	1.29	0.68	0.52	BDL	BDL
Copper	0.122	0.082	0.072	BDL	BDL
Iron	0.062	0.085	0.087	BDL	BDL
Cadmium	BDL	BDL	BDL	BDL	BDL
Nickle	0.108	0.057	0.05	BDL	BDL
Cobalt	BDL	BDL	BDL	BDL	BDL

- XXVII) The project proponent shall obtain necessary prior permission of the
- Complied, Groundwater intersection Permission have been obtained from CGWA vide letter No.



	competent authorities for draw of requisite quantity of water required for the project.	CGWA/NOC/MIN/ORIG/2022/14264 Dated 07/01/2022			
xxviii)	Suitable rainwater harvesting measures on long term basis shall be planned and implemented in consultation with the Regional Director, Central Ground Water Board.	have been constructed in consultation with CGWI			
		Pond Deepening – Mahenduriya Pond Mahenduriya Pond Mahenduriya Pond After Pond Deepening			
		Recharge Well Storm Water Ponds # 3 & # 4			
	Catch drains and siltation ponds of appropriate size shall be constructed around the mineral and over burden dumps to prevent run off of water and flow of sediments directly into the Banas River and other water bodies. The water so collected shall be utilized for watering the mine area, roads, green belt development etc. The drains shall be regularly desilted particularly after the monsoon and maintained properly.	 Garland drains have been constructed around the waste dump area along with a collection sump to prevent run off of water and flow of sediments directly into the Banas River and other water bodies. Collected water is being utilized for watering the mine area, roads, green belt development etc. The drains are regularly desilted particularly after the monsoon and maintained properly. 			
	Garland drains, settling tanks and check dams of appropriate size, gradient and length shall be constructed around the mineral and over burden dumps to	Complied. Garland drains have been constructed around the waste dump area along with a collection sump to prevent run off of water and flow of sediments			



prevent run off of water and flow of sediments directly into the Banas River and other water bodies and sump capacity shall be designed keeping 50% safety margin over and above peak sudden rainfall (based on 50 years data) and maximum discharge in the area adjoining the mine site. Sump capacity shall also provide adequate retention period to allow proper settling of silt material. Sedimentation pits shall be constructed at the corners of the garland drains and desilted at regular intervals.

- directly into the Banas River and other water bodies.
- Collection sump capacity was designed keeping all safety measures and adequate retention period to allow proper settling of silt material.
- The drains are regularly desilted particularly after the monsoon and maintained properly.

using Vertical Retreat Mining (VRM) and Blast Hot Stopping (BHS) with back filling. Concentration and

separation of Lead and Zine minerals shall be carried out in the beneficiation plant.

Complied

- Underground mining is being carried out by using Vertical Retreat Mining (VRM) and Blast Hot Stopping (BHS) with backfilling.
- Lead Zinc mineral is being concentrated and separated in the Beneficiation Plant.



Underground RD mines

XXXII) Controlled blasting practice shall be adopted. The mitigative measures for control of ground vibrations and to arrest fly rocks and boulders shall be implemented.

Complied

- Controlled blasting is adopted. Same practice will be continued.
- Various mitigative measures for control of ground vibrations have being adopted.
- Being Underground mine there is no fly rocks and boulders generation.
- Photos of Ground Vibrations control and monitoring



		Instrument used for ground vibration monitoring
XXXIII	Wet drilling blasting method and provision for the control air emissions during blasting using dust collectors etc. shall be used.	Complied, Wet drilling Controlled blasting is being adopted to control air emissions and same practice will be regularly followed. Wet Drilling
xxxiv)	Blast vibration shall be assessed from proposed operation. Ground subsidence and mine stability shall also be monitored on regular basis.	 Wet drilling Controlled blasting is being adopted in mining and the same practice will be regularly followed. Blast vibrations, Ground subsidence and mine stability are being continuously observed.
XXXV)	Regular monitoring of subsidence movement on the surface over working area and impact on water bodies/vegetation/ structures/	Regular subsidence-monitoring is carried out on surface on top of mining area, till date no



	surrounding shall be continued till movement ceases completely. In case of observation of any high rate of subsidence movement, appropriate measures shall be taken to avoid loss of life and material. Cracks shall be effectively plugged with ballast and clayey soil/suitable material.	 Measurements show negligible disturbance of less than 1 mm. All underground voids are promptly filled with cemented fill material.
xxxvi)	All the mine entries shall be above the highest flood level to avoid any anticipated flooding of mine from the surface water during the rainy season.	 Presently all the mine entries are above the highest flood level. HFL is 488.4 mRL. Main shaft collar & Auxiliary shaft collar are at 501 mRL and 496 mRL respectively.
xxxvii)	In areas where subsidence is anticipated in shallow mineral occurrence, such areas be identified and provided with garland drains to ensure draining of water and avoid ingress of the same in to the underground mine.	 Complied, In area where any subsidence is anticipated, the areas are fenced along with garland drains to ensure draining of water and avoid ingress of the water in underground mine.
xxxviii)	The project authorities shall check the possibility of existence of fault(s) before deciding about the thickness of safe barrier required to be maintained between the working face and the water bodies, if any, in consultation with the Director General Mines & Safety (DGMS). De-pillaring shall also be carried out after taking prior approval of the DGMS.	 Complied The stipulation is being complied with as per the DGMS guidelines. De pillaring, if required, is done with due approval from DGMS.
xxxix)	All the fly ash shall be utilized as per Fly Ash Notification, 1999 subsequently amended in 2003. Fly ash shall be provided to cement / brick manufacturing units for further use in making Pozollona Portland Cement (PPC).	 All the Fly Ash is utilized as per the Fly ash Notification and is being provided to cement manufacture for formation of PPC cement. Fly Ash return for financial year 2022-23 has been submitted in vide letter No. HZL/DSC/ENV/FLY ASH Return/2022-23 Dated -19.04.2023.
xl)	Mine waste shall be dumped in mine voids. Overburden due to mine expansion shall be dumped at a designated place. Waste rocks generated due to mining activity shall be utilized	Mine waste is used for height rising of the tailing dam and construction of roads. Tailings generated from Beneficiation plant being



in construction and enhancement of tailing dam. In beneficiation plant, existing tailing dam shall be used for disposal of tailings.	disposed of in tailing dam.
The solid waste generated in the form Jarosite shall be stabilized as Jarofix and disposed off in Jarofix disposal yard inside the plant premises. Cobalt cake, cooler cake, anode mud, enrichment cake, ETP sludge and spent catalyst etc. shall be disposed off in secured landfill (SLF). Waste/used oil shall be sold to registered recyclers.	 Major waste Jarosite is being generated during extraction of zinc ore concentrate by hydrometallurgy operations (hydro plant). Jarosite is mixed with 2% lime and 12-14% cement which results stable material called Jarofix which is being disposed in HDPE lined Jarofix Disposal Yard in systematic way. The above technology supplied by M/s CEZ, Canada. The advantage of Jarofix is having much improved density and physic-mechanical properties and reduce reachability of the heavy metals. The design of HDPE lined Jarofix Disposal yard is approved by RSPCB. Anode mud is being recycled back into the process and surplus, if any is sold to registered recycler. Fly Ash generated from Power plant is being provided to cement manufacture. Bottom ash is being provided to bricks manufacturer. Cooler Cake and ETP sludge after stabilization is being disposed into SLF. Piezometers are provided at down/up stream of Secured land fill and Jarofix. Regular third-party monitoring of the ground water collected from piezometers by M/s Eko Pro, which is MOEF&CC accredited laboratory. Waste/used oil is being sold to registered recyclers.





Used Oil Storage



Organic Waste Converter



Secured Landfill



Jarofix Yard

xlii)

ETP Sludge in the form of cake shall be disposed to the captive SLF. Jarosite shall be treated by mixing lime and cement to produce Jarofix, a stable product. After stabilization, Jarofix shall be disposed in dedicated disposal yard. Cooler cake and part of lead silver residue shall be neutralized and stabilized before disposal in SLF. Anode mud, cobalt cake and purification cake shall be recycled back in the process and, if surplus, shall be sold to authorized recyclers or disposed in SLF after neutralization. Spent catalyst shall be disposed in SLF after neutralization. Lead smelter slag after fuming shall be in designated stored area alternatives shall be explored for usage in road construction and cement manufacturing.

Complied.

- ETP Sludge in the form of cake and Cooler Cake are disposed to the captive SLF after stabilization.
- Jarosite after stabilization with lime and cement is being disposed in HDPE Lined Jarofix Disposal Yard.
- Other hazardous wastes like Anode Mud, Purification Cake are being sold to authorized recyclers.

xliii)

Column Leachate Studies of the stock piles of Run-of the-mine (ROM) ore, crushed ore, tailings, Jarofix shall be carried out to ascertain the pollution potential as per details given below:

Temperature fluctuation and sunlight

Complied.

 Report on Column Leachate Studies of the stockpiles of Run-of the-mine (ROM) ore, crushed ore, tailings, Jarofix, carried out by IIT Kharagpur is submitted along with EC compliance report for Apr'12 to Sep'12 period vide letter HZL



xlv)

Six Monthly EC Compliance Report (October 2022- March 2023, Hindustan Zinc Limited, Dariba Integrated Project, Village Dariba, Tehsil - Railmagra, Dist. - Rajsamand, Rajasthan

exposure under co	nfined	and	unconfined
conditions.			

Buried conditions

Air circulation

Dry - wet conditions in both confined and unconfined situations

Temperature episodes and leachate release conditions

Leachate environmental residence study

The leachate shall be measured for heavy metals for cations viz. As, St, Ni, Cu, Sb, Cr, Hg, Fe, Al, Pb, Zn, Au and Ag and anions viz. Sulfate, Chloride, Fluorine, Carbonate, Bicarbonate, Phosphate. The primary and secondary organics (Poly Aromatic Hydrocarbons) shall also be monitored in Jarofix and fresh tailings. Reports prepared shall be submitted to the Ministry within 6 months of operation of the plant.

/DSC/ENV/2012/8/24.11.2012. (Report is again attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.)

 Monitoring of Primary and Secondary organics (Poly Aromatic Hydrocarbons) and various anions and cations in Jarofix/Jarosite and Fresh tailings. Report is again attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022.

xliv) The tailing dam shall be provided with HDPE lining. Tailing dam stability, risk assessment and disaster risk mitigation & planning studies shall be conducted in the likely affected zone.

Complied.

- HDPE lining is being provided in tailing dam.
- Tailing Dam and SLF stability, risk assessment and disaster risk mitigation & planning studies are conducted, and report is again attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022

A complete hazards and risk assessment, and mitigation studies of the areas where hazardous substances are stored shall be carried out by approved agencies having qualified personnel. All plants identifiable hazardous areas like Sulfuric acid plants shall be color coded in "Red" and shall be made safe from any eventual spill or leakage. Regular inspection of the site shall be carried out.

Complied.

- HAZOP study has been carried out by M/s Safety Consultancy Services, Mumbai.
- Recommendations of the report are implemented.
- Sulphuric Acid Plant has been color coded in "Red" and made safe from any eventual spill or leakage.
- Regular site inspection is being carried out for all sites.

Hazard and risk assessment are being carried out regularly and report is attached in Six monthly compliance report (HZL/RDC/EC-CR/2021-22/H2) dated 26.05.2022



xlvi)	In the mine sites, proper delineation of the confined and unconfined aquifers, permanent surface water bodies (having more than 1 ft standing water for at least 240 days in a year) within the lease hold area and within 3 kms radius of any potential mine site have to be shown in a map. Action plan shall be prepared for the protection of aquifers in the mine area during process of mining and submitted to the Ministry and its Regional Office at Lucknow.	Complied, No such surface water body exist having more than 1 ft standing water for at least 240 days in a year within the lease hold area and within 3 kms radius of any potential mine site.
xlvii)	The top soil, if any, shall temporarily be stored at earmarked site(s) only and it shall not be kept unutilized for long. The topsoil shall be used for land reclamation and plantation.	Not applicable as mine is underground, therefore, no topsoil is not generated.
xlviii)	The over burden generated during the mining operation shall be stacked at earmarked dump site(s) only and it shall not be kept active for a long period of time and its phase-wise stabilization shall be carried out. There shall be one external over burden dump. Proper terracing of the OB dump shall be carried out so that the overall slope of the dump shall be maintained to 28°. The over burden dump shall be scientifically vegetated with suitable native species to prevent erosion and surface run off. Monitoring and management of rehabilitated areas shall continue until the vegetation becomes self-sustaining. Compliance status shall be submitted to the Ministry of Environment & Forests and its Regional Office located at Lucknow on six monthly basis.	 One external overburden dump at mine site with 10-meter height and overall slope of 28° is maintained. Two nos. of inactive dumps are rehabilitated with plantation. Strengthening of Green cover on the inactive dump is being ensure.
xlix)	Pre-placement medical examination and periodical medical examination of the workers engaged in the project shall be carried out and records maintained. For the purpose, schedule of health examination of the workers shall be	 Complied Medical examination of all the workers engaged is carried out and records are maintained as per the rules. The main tests include in PME are Audiometry,



drawn and followed accordingly.

1) As proposed, plantation shall be raised in an area of 33 % ha. Including a 7.5 m wide green belt in the safety zone around the mining lease, over burden dump, around beneficiation plant, around tailing dam, roads etc. as per Pollution Control Central guidelines by planting the native species around the periphery of plant and township, canopy based green belt shall be developed in consultation with the local DFO/Agriculture Department. The density of the trees shall be around 1,500 plants per ha.

Lung function & X- Ray.

Complied

- 33% of acquired area has been covered under plantation and the same is being maintained.
- Native plant species with long life are being planted as per CPCB guidelines and consultation with DFO.
- SO2 resistant plant species are being selected for plantation.
- The density of the trees is around 1500 plants per ha.
- Gap filling plantation is being carried out yearly to maintain the >95% survival rate of the plantation.



Panoramic View of Industrial Area with Green Belt



Plantation Near Main Gate



Plantation CPP Boundary Wall



Plantation near Community Centre



Plantation opposite Residential Colony



		Plantation – In front of CDSS Plantation – Parking Area
li)	Action plan for the mining, management of over burden (removal, storage, disposal etc.), reclamation of the mined-out area etc. shall be submitted to the Ministry and its Regional Office at Lucknow. A final mine closure plan along with details of Corpus Fund shall be submitted to the Ministry of Environment & Forests 5 years in advance of final mine closure for approval.	 Noted for Compliance. Presently, Mining is in operational stage and have sufficient Reserves and Resources for the long term mine life. Progressive Mine Closure Plan is part of Approved Mine Plan and all the measures are under implementation as per approved plan. Approved Final Mine closure along with sufficient corpus fund will be submitted to Regional Office, MOEF&CC, Lucknow, 5 years in advance of mine closure.
lii)	Conservation Plan for Schedule-I animals as per Wildlife Protection Act, 1972, if found in the study area shall be prepared and implemented on priority before commission the project for the conservation of wild fauna in consultation with the State Forest & Wildlife Department.	Omplied. No schedule-I animals are found in the core and buffer zone. Being responsible company, various conservation measures for flora and fauna are being implemented in and around the project area.
liii)	Regular medical examination and health monitoring of all the employees for Lead (Pb) and Cadmium (Cd) shall be carried out and if cases of presence of Lead (Pb) and Cadmium (Cd) are detected, necessary compensation shall be arranged under the existing laws. A competent occupational health physician shall be appointed to carry out medical surveillance. Occupational health of all the workers shall be monitored for relevant parameters and records maintained for at least 40 years from the	 A full-fledged occupation health center with qualified doctor is established in the project site. All personnel working in the Lead plant undergo test for Lead and Cadmium in Blood, to ensure early detection and rehabilitation if required. The records are being maintained as stipulated.



	beginning of the employment or 15 years after the retirement or cessation of employment whichever is later.					
liv)	All the recommendations made in Charter for Corporate Responsibility for Environment Protection (CREP) for Zinc smelters shall be implemented.		SO2 levels are ensured below the liming kg/ton Sulphuric acid produced and lower than 50 mg/Nm3. Compliance of recommendations made if for Corporate Responsibility for Engretection (CREP) for Zinc smelter submits Six monthly compliance report (HZL/CR/2021-22/H2) dated 26.05.2022	n Charter vironment		
lv)	Overall proper housekeeping shall be ensured in all the plant areas viz. Zinc and Lead smelter, Beneficiation plant, Captive power plant and other processing plant areas. The Company shall improve overall housekeeping by asphalting the internal roads and to reduce the generation of fugitive dust from vehicle movements.		Internal roads have been concreted/ asphalted to reduce the dust emission. The roads are being swept through road sweepers and cleaned with water.			
Ĭvi)	Adequate funds shall be earmarked towards capital cost and recurring expenditure per annum and a break up shall be submitted to the Ministry covering all aspects of the environment pollution control measures including extensive tree plantation on the mine and plant sites with an objective to achieve 33 % green cover within 3 years of project completion and recurring		Adequate funds are allocated for cap revenue expenditures and no fund is di other jobs/places. Environmental control measure ex breakup for FY2022-23 and Funds e towards environmental control meas FY2023-24 has been attached as Anney and Annexure XIV.	penditure armarked ures for		
	expenditure/annum for adequate pollution control measures with on-line motoring systems, ETPs, SWTPs, sound and vibration control, social forestry,	S.No	Description (Funds earmarked towards environmental control measures for FY 2023-24)	Total Amount (Rs. In Lakhs)		
	rain water harvesting, occupational health, employment of environmental cadre personnel for continuous	1	Green Belt Development, Maintenance of old plantation & landscaping	719.2		
	improvement etc.	2	Environment Monitoring	179.8		
	mprovenient etc.	3	Storm water ponds operations and maintenance & Monsoon management	76.0		
		4	Environmental training, awareness and publicity	29.3		



		- 5	Hazardous Waste Management 20)40.9
		6	Many Control of the C	3.0
		7		1.0
		8		87.0
		9		22.0
			Grand Total 33	368.2
lvii)	Rehabilitation and Resettlement Plan for the project affected population including tribals, if applicable, as per the policy of the State Govt. in consultation with the State Govt. of Rajasthan shall be implemented. Compensation paid in any case shall not be less than the norms prescribed under the National Resettlement and Rehabilitation Policy, 2007.	•	Noted for compliance, as of now no Rehabilita and Resettlement Plan applicable for this proje	
viii)	All the safety norms stipulated by the Director General, Mine & Safety (DGMS) shall be implemented.	٠	Compliance of all safety norms stipulated DGMS is being implemented.	i by
lix)	All the recommendations made in the Charter on Corporate Responsibility for Environment Protection (CREP) for the Smelters, thermal power plants and mining shall be implemented.	Co •	SO2 levels are ensured below the limit of 1.5 k. Sulphuric acid produced and acid mist lower 50 mg/Nm3. Compliance of recommendations made in Ch. for Corporate Responsibility for Environ Protection (CREP) for Zinc smelters, The Power Plants and mining was submitted with monthly compliance report (HZL/RDC CR/2021-22/H2) dated 26.05.2022	than narte men erma h six
lx)	The company shall comply with the commitments made during public hearing / consultation meeting held.	٠	Complied, all commitments made during P Hearing/consultations are being complied.	ublic
lxi)	No change in mining technology and scope of working shall be carried out without prior approval of the Ministry.	•	Noted for compliance, No further expansio modification of the plant and change in mitechnology will be carried out without approval of the Ministry.	ining
lxii)	The company shall provide housing for construction labour within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water,	•	Noted for compliance, No any major constructi going on the site. However, various labors residing on the colony area. Basic facilities provided.	are



B. i)	the completion of the project. EC General Conditions The project authorities must strictly adhere to the stipulations made by the Rajasthan State Pollution Control Board (RSPCB) and the State Government. No expansion or modifications in the plant shall be carried out without prior approval of the Ministry of Environment	Complied, Consent to operates have been obtained from the Rajasthan State Pollution Control Board (RSPCB) and all the conditions stipulated therein are being implemented. Noted for Compliance, No further expansion of modification of the plant and change in mining.				rol Board ed therein ansion or in mining
1117	and Forests.	 Third Party Periodical monitoring of various parameters i.e. PM10, PM2.5, NOx and SO2 are being done in the ambient air within the impactione. Ambient Air Quality Monitoring Stations (AAQMS) have been established. Third party monitoring of Ambient air quality carried out by Third party, which is NABL and MoFF&CC accredited laboratory. 				our prior
iii)	Adequate number of ambient air quality-monitoring stations shall be established in the downward direction as well as where maximum ground level concentration of SPM, SO2 and NOx are anticipated in consultation with the Rajasthan State Pollution Control Board. Data on ambient air quality and stack emission shall be regularly submitted to this Ministry including its Regional Office at Lucknow and the State Pollution Control Board/Central					
	Regional Office at Lucknow and the State Pollution Control Board/Central	MoE	ed out by	nitoring of Γhird party,	which is N	
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	MoE	ed out by	nitoring of Γhird party,	which is N tory.	
	Regional Office at Lucknow and the State Pollution Control Board/Central	MoE	ed out by	Observed Near Storm Water	which is N tory.	
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	MoE. Parameters (µg/ m3)	Near Main Gate	Observed Near Storm Water pond	which is Notory. Value Near CPP Area	Near SLF Area
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	Parameters (µg/ m3)	Near Main Gate	Observed Near Storm Water pond 78.84	which is Notory. Value Near CPP Area	Near SLF Area
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	MoE. Parameters (µg/ m3)	Near Main Gate	Observed Near Storm Water pond 78.84 40.19	Which is Notory. Value Near CPP Area 78.30 39.71	Near SLF Area 82.40 40.33
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	Parameters (µg/ m3) PM10 PM2.5	Near Main Gate	Observed Near Storm Water pond 78.84	which is Notory. Value Near CPP Area	Near SLF Area
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	Parameters (µg/ m3) PM10 PM2.5 SO2	Near Main Gate 82.44 44.70 15.65	Observed Near Storm Water pond 78.84 40.19 16.78	Which is Notory. Value Near CPP Area 78.30 39.71 14.79	Near SLF Area 82.40 40.33 15.14
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	Parameters (µg/ m3) PM10 PM2.5 SO2 NO2	Near Main Gate 82.44 44.70 15.65 27.78	Observed Near Storm Water pond 78.84 40.19 16.78 31.52	Which is Notory. Value Near CPP Area 78.30 39.71 14.79 26.48	Near SLF Area 82.40 40.33 15.14 26.43
	Regional Office at Lucknow and the State Pollution Control Board/Central Pollution Control Board once in six	Parameters (µg/ m3) PM10 PM2.5 SO2 NO2 CO	Near Main Gate 82.44 44.70 15.65 27.78 0.95	Observed Near Storm Water pond 78.84 40.19 16.78 31.52 0.90	which is N tory. Value Near CPP Area 78.30 39.71 14.79 26.48 0.88	Near SLF Area 82.40 40.33 15.14 26.43 0.87

 Average Ambient Air Quality Monitoring results for mine are enclosed herewith as Annexure II and



POR RICK POR	Rajsamand, Rajasthan	
	Kajsamand, Kajastnan	 for DSC as Annexure III. Eight nos. of AAQMS have been established at buffer zone for ambient air quality monitoring are enclosed as Annexure IV. Zero discharge is being maintained. The monitored data have been displayed on display board at the project site and also on Company website along with Six Monthly Environment Compliance report. Link of the report is https://www.hzlindia.com/sustainability/environment-compliance/ Six Monthly Environment Compliance report along with all Analysis reports for the ambient,
	Industrial wastewater shall be properly collected, treated so as to conform to the standards prescribed under GSR 422 (E) dated 19th May, 1993 and 31st December, 1993 or as amended form time to time. The treated wastewater should be recycled in the plant as well as utilization for plantation purposes.	stack and fugitive emission are enclosed and being submitted to the Regional Office, MOEF&CC Lucknow, CPCB and RSPCB. Complied Industrial waste water is properly collected, treated in the ETP (capacity 9000KLD) followed by double stage RO (capacity 8850 KLD) and MEE 600 KLD capacity so as to confirm treated water quality as per the prescribed standards and recycled back in the plant as well as utilized for plantation purposes.
		 Details of ETP plant has been submitted along with six monthly compliance report vide letter no HZL/DSC/Env/2011/2/2 dated 23.11.2011. Zero Discharge is being maintained.
v)	The project authorities must strictly comply with the rules and regulations with regard to handling and disposal of hazardous wastes in accordance with the Hazardous Wastes (Management and Handling) Rules, 2003. Authorization from the State Pollution Control Board must be obtained for collection, storage, treatment and disposal of hazardous wastes.	 Complied Hazardous waste Authorization under Hazardou Waste and other Waste (Management and Handling & Transboundary) Rules, 2016 has been obtained from RSPCB. Hazardous Wastes are properly collected and stored in dedicated area before handed over the authorized vendor. Jarosite is mixed with 4% lime and 12-14% cemer which results stable material called Jarofix which is being disposed in HDPE lined Jarofix Disposation.

Yard in systematic way.



		 Anod mud is being reuse/ sold to registered recycler. Fly Ash generated from Power plant is being provided to cement manufacture. Bottom ash is being provided to bricks manufacture Cooler Cake and ETP sludge after stabilization is being disposed into SLF.
vi)	The overall noise levels in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise levels should conform to the standards prescribed under EPA Rules, 1989 viz. 75 dBA (daytime) and 70 dBA (nighttime).	 Waste/used oil is being sold to registered recycler. Complied Noise control measures including acoustic hoods, silencers, enclosures etc. have been provided on all sources of noise generation. Noise levels in and around the plant area are being monitored regularly and utmost care is taken to ensure that noise level remains below the norms. Average noise monitoring report is furnished herewith as Annexure XI.
vii)	Occupational Health Surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	 A full-fledged occupation health center with qualified doctor is established in the project site. All personnel working in the Lead plant undergo test for Lead and Cadmium in Blood, to ensure early detection and rehabilitation if required. The records are being maintained as stipulated.
viii)	The project proponent shall also comply with all the environmental protection measures and safeguards recommended in the EIA/EMP/risk analysis and DMP report.	 Complied Environmental protection measures and safeguards recommended in the EIA/EMP/risk analysis and DMP report are being implemented. For emission control, ESP, Bag houses, Venturi, eyelone and gas wash tower have been installed with adequate stacks height for proper dispersion of emission. For Effluent, Control, zero discharge is being maintained through ETP, Double stage RO and MEE plants. For Hazardous waste management, best available technology being used for waste minimization and disposal of Hazardous waste is being done as per Authorization conditions.



ix)	As proposed, Rs. 230.00 Crores and Rs. 1.20 Crores shall be earmarked towards total capital cost and recurring cost/annum for environmental pollution control measures to implement the conditions stipulated by the Ministry of Environment and Forests as well as the State Government along with the implementation schedule for all the conditions stipulated herein. The funds so provided should not be diverted for any other purposes.	 Adequate funds are allocated for capital and revenue expenditures and no fund is diverted to other jobs/places. 			
		S. No.	Description (Expenditure towards environmental control measures for FY 2023-24)	Total Amount (Rs. In Lakhs)	
		1	Green Belt Development, Maintenance of old plantation & landscaping	719.2	
		2	Environment Monitoring	179.8	
		3	Storm water ponds operations and maintenance & Monsoon management	76.0	
		4	Environmental training, awareness, and publicity	29.3	
		5	Hazardous Waste Management	2040.9	
		6	O&M of Organic waste Convertor	3.0	
		7	Environmental Audit & IMS	11.0	
		8	Returns, Fees for Award & CTO	187.0	
		9	Pollution control measures	122.0	
			Grand Total	3368.2	
x)	A copy of clearance letter shall be sent by the proponent to concerned Panchayat, Zila Parishad/ Municipal Corporation, Urban Local Body and the local NGO, if any, from whom suggestions/ representations, if any, were received while processing the proposal. The clearance letter shall also be put on the web site of the company by the proponent.	 Complied and communicated to Regional Office. MoEF vide letter no: HZL/RDM/Env/2009/898 dated 20.11.2009. 			
xi)	The project proponent shall upload the status of compliance of the stipulated environment clearance conditions, including results of monitored data on their website and shall update the same periodically. It shall simultaneously be sent to the Regional Office of the		Status of compliance of the stipulated environment clearance conditions, including results of monitored data are being furnished regularly to the Regional Office, MOEF&CC, CPCB and RSPCB. Critical environmental parameters are being		

displayed near the main gate and company website

along with six monthly compliance reports, Link of

MOEF at Lucknow, the respective

Zonal Office of CPCB and the RSPCB.



Six Monthly EC Compliance Report (October 2022- March 2023, Hindustan Zinc Limited, Dariba Integrated Project, Village Dariba, Tehsil - Railmagra, Dist. - Rajsamand, Rajasthan

	The criteria pollutant levels namely; SPM, RSPM, SO2, NOx (ambient levels as well as stack emissions) or critical sectoral parameters, indicated for the projects shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.	the report is https://www.hzlindia.com/sustainability/environment-compliance/
xii)	The project proponent shall also submit six monthly reports on the status of the compliance of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by e-mail) to the Regional Office of MOEF, the respective Zonal Office of CPCB and the RSPCB. The Regional Office of this Ministry at Lucknow / CPCB / RSPCB shall monitor the stipulated conditions.	 The monitored data has been displayed on the display board at the project site and on the Company website along with Six Monthly Environment Compliance report. Link of the report is https://www.hzlindia.com/sustainability/environment-compliance/ Six Monthly Environment Compliance report along with all Analysis reports for the ambient, stack and fugitive emission are enclosed and being submitted to the Regional Office, MOEF&CC Lucknow, CPCB and RSPCB.
xiii)	The environmental statement for each financial year ending 31st March in Form-V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as prescribed under the Environment (Protection) Rules, 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance of environmental conditions and shall also be sent to the respective Regional Offices of the MOEF by e-mail.	 Environmental Statement (Form-V) of Financial Year 2021-22 is submitted on date 22.09.2022 via letter number: HZL/DSC/ENV/ES/2022/1 for Zinc, HZL/DSC/ENV/ES/2022/2 for Lead. & HZL/DSC/ENV/ES/2022/3 for CPP. Environmental Statement (Form-V) of Financial Year 2021-22 is displayed on the Company website along with Six Monthly Environment Compliance report. Link of the Form V is https://www.hzlindia.com/sustainability/environment-compliance/
xiv)	The Project Proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the RSPCB and may also be seen at Website of the Ministry of Environment and Forests at http://envfor.nic.in. This shall be advertised within seven days from the	 Complied, Press advertisement published in local newspapers (hindi) i.e. Rajasthan Patrika & Dainik Bhasker (Rajsamand edition) on 08.11.09 and has been communicated to Regional Office, MoEF vide letter no: HZL/RDM/Env/2009/898 dated 20.11.2009.



Six Monthly EC Compliance Report (October 2022- March 2023, Hindustan Zinc Limited, Dariba Integrated Project, Village Dariba, Tehsil - Railmagra, Dist. - Rajsamand, Rajasthan

	date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locality concerned and a copy of the same should be forwarded to the Regional office.	
xv)	Project authorities shall inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of commencing the land development work.	Complied.
Enviro	onment Clearance Letter no.: J-11015/380/200 ction from 0.9 MTPA to 1.08 MTPA	3-IA II (I) dated 26.7.2018 for Expansion of Lead Zinc Or
1	The environmental clearance will not be operational till such time the project proponent complies with all the statutory requirements and Judgement of Hon'ble Supreme Court dated 2nd August 2017 in Writ Petition (Civil) No: 114 of 2014 in the matter of Common Cause versus Union of India and Ors, if any, applicable to this project.	Noted and Complied.
2.	The Department of Mines and Geology, Government of Rajasthan shall ensure that mining operations shall not commence till the entire compensation levied, if any, for illegal mining paid by the Project Proponent through their respective department of Mines and Geology in strict compliance of Judgement of Hon'ble Supreme Court dated 2nd August 2017 in Writ Petition (Civil) No: 114 of 2014 in the matter of Common Cause versus Union of India and Ors.	Noted and Complied.
3.	All other specific and general conditions mentioned in the Ministry's EC Letter No: J-11015/380/2008-IA-II(M) dated 4.11.2009 shall remain the same.	Noted and Complied.

Annexure I

Hindustan Zinc Limited Dariba Smelter Complex Dariba, Dist. Rajsamand, Rajasthan.

SO₂ Continuous Monitoring Report (October'22-March'23)

Month Location	Parameters	Prescribed Limits	Oct'22	Nov'22	Dec'22	Jan'23	Feb'23	Mar'23
Acid Plant* (Zinc Smelter) Roaster-1	SO ₂ (Kg/T of H ₂ SO ₄ Production)	1.5	0.80	0.81	0.85	0.86	0.79	0.73
Acid Plant* (Zinc Smelter) Roaster-2	SO ₂ (Kg/T of H ₂ SO ₄ Production)	1.5	1.09	1.03	1.10	1.04	1.03	0.99
TGT Stack (Lead Plant)	SO2 (Kg/T of H2SO4 Production)	1.5	0.19	0.20	0.14	0.11	0.11	0.12

(Vivek Kumar)

Head Environment

Dariba Smelter Complex



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

Office 6 Charactery 35-41 South Side of G. T. Royal (ESIDE Industrial Area Charactery - 201 089 (Esistemos Report Contact No. 97 (11997)) 9991(40537-981)(240678-5 man small@existence.com (Report Contact No. 97 (11997)) 9991(40537-981)(240678-5 man small@existence.com (Report Contact No. 97 (11997)) 9991(40537-981)(240678-5 man small@existence.com)

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/039/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Raiasthan

Sample Description : Stack Emission
Sample Drawn on : 24/12/2022

Sample Drawn on : 24/12/2022
Sample Drawn by : EPEPL (Mr. Umesh Kumar)

Sample Received on : 27/12/2022 Time of Sampling (minutes) : 30.0

Sampling Location : NA

Sampling Plan & Procedure : SOP-SE/09

Analysis Duration : 27/12/2022 To 31/12/2022

Source of Emission : Stack Attached To Zinc Smelter Roaster (R-4)**

Capacity : _
Operating Load : Normal

Normal Operation Schedule : As per requirement

Type of Stack : MS
Diameter of Stack (meter) : 2.5
Height of Stack from Ground Level (meter) : 100.

Height of Stack from Ground Level (meter) : 100.0
Height of Stack from Roof Level (meter) : Height of Sampling Location (meter) : -

Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C)

Stack Temperature (°C)

58.0

Average Velocity of Fuel Emission (m/sec) : 6.2
Average Flow Rate (lpm) : 28.7
Control Measures (if any) : Nil

Remark (if any) : ** Acid Plant Attached with DCDA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Sulphur Dioxide (as SO ₂)	IS: 11255 (P-2)	420.9	mg/Nm ³	950.0
2	Acid Mist (as H2SO4)	USEPA Method 8	33.5	mg/Nm ³	50.0

Notes

- The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only,

** End of Report **

For EKO PRO ENGINEERSIPAT, LTD.
PURIMBAL BHAUHAN
TEGHNICAL MANAGER
(Authorised Signatory)

Page 1 of 1



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISC 9001:2015 Certified Company)

Office & Estateston (1911) Share State of S. 1. Roug, UPSIDC Industrial May Officeable (1911) 709 (DemiNCR) migra-Control No. 97 (1994) 0 (M1)249637, 981 (249678) Share impropersion in ecopyographic pages 8 followers (

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/035/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description : Stack Emission
Sample Drawn on : 24/12/2022

Sample Drawn by : EPEPL (Mr. Umesh Kunar)

Sample Received on : 27/12/2022 Time of Sampling (minutes) : 30.0

Sampling Location : NA

Sampling Plan & Procedure : SOP-SE/09
Analysis Duration : 27/12/2022 To

Analysis Duration : 27/12/2022 To 31/12/2022
Source of Emission : Stack Attached To Zinc Smelter Roaster (R-5)**

Capacity : _

Operating Load : Normal

Normal Operation Schedule : As per requirement

Type of Stack : MS
Diameter of Stack (meter) : 2.5
Height of Stack from Ground Level (meter) : 100.0
Height of Stack from Roof Level (meter) : -

Height of Sampling Location (meter)
Type of Fuel Used

Average Flow Rate (Ipm) : 19.2 Control Measures (if any) : Nil

Remark (if any) : ** Acid Plant Attached with DCDA


RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Sulphur Dioxide (as SO ₂)	IS: 11255 (P-2)	392.8	mg/Nm³	950.0
2	Acid Mist (as H2SO4)	USEPA Method 8	32.7	mg/Nm ³	50.0

Notes

- The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **





EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certifled Company).

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/033/271222

Issued To

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Time of Sampling (minutes)

Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter) Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour Ambient Temperature (°C)

Stack Temperature (°C) Average Velocity of Fuel Emission (m/sec)

Average Flow Rate (lpm) Control Measures (if any)

Remark (if any)

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Stack Emission : 23/12/2022

: EPEPL (Mr.Umesh Kumar)

: 27/12/2022

: 30.0 : NA

: SOP-SE/09

: 27/12/2022 To 31/12/2022

: Stack Attached To Zinc Dross

: Normal

: As per requirement

: MS : 1.3

: 30.0

5 -: 18.0

: 48.0 : 6.0

: 22.4 : Nil

NA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	24.9	mg/Nm ³	50.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

The test report will not be used for any publicity/legal purpose.

- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

"* End of Report ""

For EKO PRO ENGINEERS PVT. LTD. PURNIMA CHAUHAN TECHNICAL MANAGER (Authorised Signatory)



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/034/271222

Issued To

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Time of Sampling (minutes)

Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter)

Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter)

Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C)

Stack Temperature (°C) Average Velocity of Fuel Emission (m/sec)

Average Flow Rate (Ipm)

Control Measures (if any)

Remark (if any)

: HINDUSTAN ZINC LIMITED

Stack Emission

23/12/2022 EPEPL (Mr. Umesh Kumar)

27/12/2022

30.0

NA.

SOP-SE/09

27/12/2022 To 31/12/2022

Stack Attached To Zinc Dust Plant with Bag House

As per requirement

: MS

0.5

30.0

18.0

72.0

23.9

21.4

: Nil NA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	35.2	mg/Nm ³	50.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

3. The test report will not be used for any publicity/legal purpose.

 The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer

Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

Analytical Septicals (ACC), of Engineering Control (ACC), (VISH), Control (See Marine), Control (Septical Septical Septi

FOR EKO PRO ENGINEERS PVT, LTD. PURNIMA CHAUHAN TECHNICAL MANAGER (Authorised Signatory)



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certifled Company)

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/027/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by Sample Received on

Time of Sampling (minutes) Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter) Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour Ambient Temperature (°C)

Stack Temperature (°C) Average Velocity of Fuel Emission (m/sec)

Average Flow Rate (Ipm) Control Measures (if any)

Remark (if any)

Stack Emission

: 22/12/2022

: EPEPL (Mr. Umesh Kumar)

27/12/2022

30.0 - NA

SOP-SE/09

27/12/2022 To 31/12/2022

Stack Attached To Lead Electro Refinery Plant (Pyro)**

: Normal

: As per requirement

: MS

2.0 40.0

: 18.0 : 124.0

: 5.8

: 21.9 : Nil

: "South Lead Plant Attached to Bag Filter

RESULTS.

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
4	Particulate Matter (as PM)	IS 11255 (P-1)	32.8	mg/Nm ³	50.0
2	Lead (as Pb)	USEPA (P-12)	3.11	mg/Nm ³	10.0

1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only

2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory

The test report will not be used for any publicity/legal purpose.

4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer:

5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT. LTD. PURNIMA CHADHAN TECHNICAL MANAGER (Authorised Signatory)

Page 1 of 1



EKO PAO ENGINEERS PVT.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

Office X Laboratory - XEAT Scam Sels of G. 7. HAND, IMPRIDE Industrial Again Contralable - 197 009 (Contral ACP) Indige Contral No. 9711 SQL 10: 98 (COMBRS7, Resolveders, Birds) | employed provide the promption of the Combrat Resolved to

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/028/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Time of Sampling (minutes) Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter)

Height of Stack from Ground Level (meter) Height of Stack from Roof Level (meter)

Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C) Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (lpm)

Control Measures (if any)

Remark (if any)

Stack Emission : 22/12/2022

: EPEPL (Mr. Umesh Kumar)

27/12/2022

: 30.0

: NA

SOP-SE/09

: 27/12/2022 To 31/12/2022

: Stack Attached To Lead Electro Refinery Plant (Pyro)**

: Normal

: As per requirement

: MS

: 2.0 : 40.0

3

0 =

: 18.0

: 142.0 6.1

: 19.2

: Nit

**North Lead Plant Attached to Bag Filter

PESILITS

THE LABOR TO SERVICE AND ADDRESS OF THE PARTY OF THE PART	INCOULTS.	Service de la company		
Parameters	Test Methods	Results	Units	Limits as per Consent
Particulate Matter (as PM)	IS: 11255 (P-1)	40.9	availed 3	A SHOUNDSON
Lead (as Ph)			mg/Nm	50.0
	USEPA (P-12)	2.86	mg/Nm ³	10.0
		Parameters Test Methods Particulate Matter (as PM) IS: 11255 (P-1)	Parameters Test Methods Results Particulate Matter (as PM) IS: 11255 (P-1) 40.9 Lead (as Ph) IS: 1255 (P-1) 40.9	Parameters Test Methods Results Units Particulate Matter (as PM) IS: 11256 (P-1) 40.9 mg/Nm³ Lead (as Pb) USERA (P.12) 0.00

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

The test report will not be used for any publicity/legal purpose.

4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.

5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PUT LTD. PURNIMA CHAUFAN TECHNICAL MANAGER (Authorised Signatory)

Page 1 of 1



ENO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/832/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Raipura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on Time of Sampling (minutes)

Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter)

Height of Sampling Location (meter)

Type of Fuel Used Fuel Consumed per hour

Ambient Temperature (°C) Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (lpm)

Control Measures (if any) Remark (if any)

Stack Emission 23/12/2022

: EPEPL (Mr. Umesh Kumar)

: 27/12/2022

: 30.0

: NA : SOP-SE/09

: 27/12/2022 To 31/12/2022

: Stack Attached To Lead Secondary Plant with Bag House (Blast Furnace)**

: Normal

As per requirement

: MS : 2.2

: 75.0

18.0

: 67.0 : 8.1

> 22.7 Nil

NA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	36.9	mg/Nm ³	50.0
2	Lead (as Pb)	USEPA (P-12)	4.18	mg/Nm ³	10.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **





EKO PAO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Cartifled Company)

Contactive 19711 57219 9870290837 0800389629 Evision and exercitive outprough configuration, as bulls investigators

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/036/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on Time of Sampling (minutes)

Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter)

Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C) Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (lpm)

Control Measures (if any)

Remark (if any)

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Stack Emission

24/12/2022

: EPEPL (Mr.Umesh Kumar)

: 27/12/2022

: 30.0

: NA

: SOP-SE/09

27/12/2022 To 31/12/2022

: Stack Attached To Lead Electro Refinery Plant (M&C)**

: Normal

: As per requirement

: MS

: 2.0

: 40.0

: 18 0

: 142.0

: 6.5

: 20.5

: NII

"North Lead Plant Attached to Bag Filter

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	33.9	mg/Nm ³	50.0
2	Lead (as Pb)	USEPA (P-12)	3.81	mg/Nm ³	10.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory

3. The test report will not be used for any publicity/legal purpose.

- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PUT LTD. PURNIMA CHARTAN TECHNICAL MANAGER (Authorised Signatory)

Page 1 of 1



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001 2015 Sertified Company)

Office & Leomatory (274), South Side of G. T. Rodo, LPSIDG Midbuthal Area, (Shazinsid - 201 009 (De)N-NCP; [ND]X Commit No. 971(1597), 9810240537, 9810240678, Edinal among south in skid-commercial conditions were shadown

TEST REPORT

Stack Emission Analysis Test Report No. : EKO/037/271222 Issue Date: 31/12/2022 issued To : HINDUSTAN ZINC LIMITED Dariba Smelter Complex Post - Dariba, District - Rajpura Dariba Mines Udaipur-Rajasthan Sample Description Stack Emission Sample Drawn on 24/12/2022 Sample Drawn by : EPEPL (Mr. Umesh Kumar) Sample Received on : 2712/2022 Time of Sampling (minutes) : 30.0 Sampling Location : NA Sampling Plan & Procedure : SOP-SE/09 Analysis Duration : 27/12/2022 To 31/12/2022 Source of Emission : Stack Attached To Lead Electro Refinery Plant (M&C)** Capacity Operating Load : Normal Normal Operation Schedule : As per requirement Type of Stack : MS Diameter of Stack (meter) : 2.0 Height of Stack from Ground Level (meter) : 40.0 Height of Stack from Roof Level (meter) Height of Sampling Location (meter) Type of Fuel Used Fuel Consumed per hour

**South Lead Plant Attached to Bag Filter

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	42.5	mg/Nm ³	50.0
2	Lead (as Pb)	USEPA (P-12)	4 92	mg/Nm ³	10.0

Notes

Ambient Temperature (*C)

Average Velocity of Fuel Emission (m/sec)

Stack Temperature (°C)

Average Flow Rate (Ipm)

Control Measures (if any)

Remark (if any)

 The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.

: 18.0

: 6.5

: 21.7

: Nil

: 114.0

2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

3. The test report will not be used for any publicity/legal purpose.

- The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- Responsibility of the Laboratory is limited to the invoiced amount only.

" End of Report "

For EKO PRO ENGINEERS PVT LTD.
PURNIMA CHAUHAN
TEGHNICAL MANAGER
(Authorised Signatory)



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

TEST REPORT

Stack Emission Analysis

Test Report No.: EKO/030/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Sample Description Sample Drawn on

Sample Drawn by

Sample Received on Time of Sampling (minutes)

Sampling Location Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter) Height of Stack from Roof Level (meter)

Height of Sampling Location (meter) Type of Fuel Used Fuel Consumed per hour

Ambient Temperature (°C) Stack Temperature (°C) Average Velocity of Fuel Emission (m/sec)

Average Flow Rate (Ipm) Control Measures (if any)

Remark (if any)

Post - Dariba, District - Raipura Dariba Mines

Udaipur-Rajasthan

Stack Emission

22/12/2022

: EPEPL (Mr. Umesh Kumar)

: 27/12/2022 : 30.0

: NA : SOP-SE/09

: 27/12/2022 To 31/12/2022 : Stack Attached To Lead Primary Plant with Bag House (SKS Furnace)

: Normal

: As per requirement

: MS : 2.0

: 75.0

: 18.0

: 65.0 7.4

; 22.1 : Nil : NA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	43.9	mg/Nm ³	50.0
2	Lead (as Pb)	USEPA (P-12)	4.18	mg/Nm ³	10.0

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

3. The test report will not be used for any publicity/legal purpose.

- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **





EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9881:2015 Certified Company)

Control No. 197 (1) 592 (0. 461024083) (Jehr) 40678 E-mail Email/Edisons in Exhibit propriet regional con metalla substitution

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/031/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description Sample Drawn on : 23/12/2022 Sample Drawn by Sample Received on : 27/12/2022 Time of Sampling (minutes) : 30 0 Sampling Location : NA Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule Type of Stack

Diameter of Stack (meter) Height of Stack from Ground Level (meter)

Height of Stack from Roof Level (meter) Height of Sampling Location (meter) Type of Fuel Used

Fuel Consumed per hour Ambient Temperature (°C) Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (lpm) Control Measures (if any)

Remark (if any)

Stack Emission

: EPEPL (Mr. Umesh Kumar)

: SOP-SE/09

: 27/12/2022 To 31/12/2022

: Stack Attached To TGT Lead Plant**

: Normal

: As per requirement : MS

: 2.0 : 100.0

: 18.0 : 74.0

: 6.9 : 18.2 Nil

** Attached to Blast Furnace, Aid Plant, CDT Input

RESULTS

	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Sulphur Dioxide (as SO ₂)	IS: 11255 (P-2)	239.8	mg/Nm³	950.0
2	Acid Mist (as H2SO4)	USEPA Method 8	20.4		930.0
otes:		COLLY Method 9	32.4	mg/Nm ³	50.0

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

The test report will not be used for any publicity/legal purpose.

4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.

5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT LTD. PURCHAMBAN TECHNICAL MANAGER (Authorised Signatory)

Page 1 of 1



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9881:2015 Cartified Company)

Contact sig., 97:3 (892-95 alctitizs) 937-98:01:40678-5 mail renalidiscoproje. Gaspoeropreed glyradicen invasital www.etcerb.wi

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/030/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description Stack Emission Sample Drawn on : 22/12/2022

Sample Drawn by : EPEPL (Mr. Umesh Kumar)

Sample Received on : 27/12/2022 Time of Sampling (minutes) 30.0

Sampling Location NA

Sampling Plan & Procedure : SOP-SE/09

Analysis Duration 27/12/2022 To 31/12/2022

Source of Emission : Stack Attached To Lead Primary Plant with Bag House (SKS Furnace) Capacity

Operating Load : Normal

Normal Operation Schedule : As per requirement

Type of Stack : MS Diameter of Stack (meter) : 2.0 Height of Stack from Ground Level (meter) : 75.0

Height of Stack from Roof Level (meter) Height of Sampling Location (meter)

Type of Fuel Used Fuel Consumed per hour Ambient Temperature (°C) : 18.0 Stack Temperature (°C) : 65.0 Average Velocity of Fuel Emission (m/sec) : 7.4

Average Flow Rate (Ipm) : 22.1 Control Measures (if any) : Nil Remark (if any) : NA

RESULTS

000-0-20	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	IS: 11255 (P-1)	43.9	mg/Nm ³	50.0
2 otes:	Lead (as Pb)	USEPA (P-12)	4.18	mg/Nm ³	10.0

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

The test report will not be used for any publicity/legal purpose.

- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PUT LTD. PURNIMA CHAVRAN JECHNICAL MANAGER (Authorised Signatory)

Page 1 of 1



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory
(An ISO 9921: 2015 CanWed Company)

Chica & Laboratory, 32941. South Selfs M.G. T. Rose, CPSt045 Patriother Appl. Briggished - 201 009 (Bern-NCR) INDIA Comput No. 07331592 to 3640240097 0840240078 Error unadebrook to all contemporal partitions with an accompany.

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/029/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

: EPEPL (Mr. Umesh Kumar)

27/12/2022 To 31/12/2022

As per requirement

Stack Attached To Coal Crusher

: Stack Emission

27/12/2022

SOP-SE/09

22/12/2022

30.0

NA

: MS

1.3

18.0

86.0

22.7

: 7.9

Sample Description Sample Drawn on

Sample Drawn by

Sample Received on

Time of Sampling (minutes) Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter)

Height of Stack from Ground Level (meter) Height of Stack from Roof Level (meter)

Height of Sampling Location (meter) Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C) Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (lpm)

Control Measures (if any) Remark (if any)

: Nil : NA

RESULTS

S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1	Particulate Matter (as PM)	(S: 11255 (P-1)	34.2	mg/Nm ³	50.0

Notes:

- The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only:
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

3. The test report will not be used for any publicity/legal purpose.

- The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

" End of Report "

For EKO PRO ENGINEERS PVT LTD.
PURNIMA CHAUHAN
TECHNICAL MANAGER
(Authorised Signatory)



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

TEST REPORT

Stack Emission Analysis

Test Report No. : EKO/038/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Time of Sampling (minutes)

Sampling Location

Sampling Plan & Procedure

Analysis Duration

Source of Emission

Capacity

Operating Load

Normal Operation Schedule

Type of Stack

Diameter of Stack (meter)

Height of Stack from Ground Level (meter) Height of Stack from Roof Level (meter)

Height of Sampling Location (meter)

Type of Fuel Used

Fuel Consumed per hour

Ambient Temperature (°C)

Stack Temperature (°C)

Average Velocity of Fuel Emission (m/sec) Average Flow Rate (ipm)

Control Measures (if any)

Remark (if any)

Post - Dariba, District - Raipura Dariba Mines

Stack Emission

24/12/2022

EPEPL (Mr. Umesh Kumar)

: 27/12/2022

: 30.0

: NA

: SOP-SE/09

: 27/12/2022 To 31/12/2022

: Stack Attached To Common Stack of CPP 2 x 85 MW**

: Normal

: As per requirement

: MS

: 4.0

: 165.0

1 -

1 -

: 18.0

: 130.0

: 22.5

: 20.9

: **(At Dust Opening Point) attached with ESP

RESULTS

-		11200210			
S.No.	Parameters	Test Methods	Results	Units	Limits as per Consent
1.	Particulate Matter (as PM)	IS: 11255 (P-1)	32.9	mg/Nm³	50.0
2	Sulphur Dioxide (as SO ₂)	(S: 11255 (P-2)	1290.7	mg/Nm ³	600.0
3	Oxide of Nitrogen (as Nox)	IS: 11255 (P-7)	210.5	mg/Nm³	300.0
4	Hg and its Compounds	APHA Method 822	<0.005	mg/Nm ³	0.03

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT. LTD. PURNIMA CHADHAN TECHNICAL MANAGERICE Lof 1 (Authorised Signatory)





Sample Number: VTL/\$/08

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270006/A

Format No

: 7.8 F-03

Party Reference No : NIL Report Date

: 30/03/2023

: 27/03/2023

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Zinc Dross

Sample Collected By

: VTL Team

Date of Sampling

: 23/03/2023

Sampling duration (Minutes)

: 38 min. (10:00 to 10:38 hrs.)

Stack attached to Make of stack

: Bag Filter Iron

Diameter of stack(m)

1.3 m

Height of stack(m)

: 30 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

: 24°C

Temperature of Stack Gases - Ts (°C)

: 25

Velocity of Stack Gases (m/sec.)

: 6.12

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

: 26

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

.No.	Parameters	Test Method	Results	Units	Limits
	Particulate Matter (PM)	IS: 11255 (P-1) : 1985, RA 2019	27.30	mg/Nm3	50.0

End of Report

RK Yadav Lab Incharge Authorized Signatory



Page No. 1/1.

Approved & Cartified PPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified







Sample Number :

VTUS/07

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udalpur Rajasthan

Report No.

: VTL/S/2303270007/A

Format No

7.8 F-03 Party Reference No : NIL

Report Date

: 30/03/2023 Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Zinc Dust Plant With Bag House

Sample Collected By Date of Sampling

: VTL Team : 22/03/2023

Sampling duration (Minutes)

: 26 min. (15:30 to 15:56 hrs.)

Stack attached to

: Bag Filter

Make of stack Diameter of stack(m)

: Iron

: 0.5 m

Height of stack(m) Instrument calibration status

; 30 m

Meteorological Condition

: Calibrated : Clear Sky

Ambient Temperature - Ta (°C)

: 28°C

Temperature of Stack Gases - Ts (°C) Velocity of Stack Gases (m/sec.)

: 67 : 23.56

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

: 39

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

No. Parameters	Test Method	Results	Units	Limits
Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019	36.92	mg/Nm3	50.0

End of Report



Checked by

AK Yadav JAIPUR bab Incharge Authorized Signatory



Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified







Sample Number :

VTL/S/08

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270008/A

Format No Party Reference No : NIL

: 7.8 F-03

Report Date

: 30/03/2023

: 27/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Zinc Smelter Roaster (R-5)

Sample Collected By

Date of Sampling

: VTL Team : 23/03/2023

Sampling duration (Minutes)

: 52 min. (10:30 to 11:22 hrs.)

Stack attached to

: Bag Filter

Make of stack

: Iron

Diameter of stack(m)

: 2.5 m

Height of stack(m)

: 100 m

Instrument calibration status Meteorological Condition

: Calibrated : Clear Sky

Ambient Temperature - Ta (°C)

: 24°C

Temperature of Stack Gases - Ts (°C)

: 79

Velocity of Stack Gases (m/sec.) Flow rate of PM (LPM)

: 6.65

Flow rate of Gas (LPM)

: 24

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
9	Sulphur Dioxide (SO2)	IS: 11255(P- 2): 1985, RA 2019	386,13	mg/Nm3	950.0
2	Acid Mist (H2SO4)	USEPA 8, 1983	33.30	mg/Nm3	50.0

End of Report

"Experience the unimaginable



Checked by





Page No. 1/1

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified







Sample Number: VTUS/11

Name & Address of the Party ; M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270011/A

Format No.

. 7.8 F-03

Report Date

Party Reference No : NIL : 30/03/2023

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Zinc Smelter (R-4)

Sample Collected By

: VTL Team

Date of Sampling

: 23/03/2023

Sampling duration (Minutes)

: 38 min. (14:00 to 14:38 hrs.)

Stack attached to

: Bag Filter

Make of stack

: Iron

Diameter of stack(m)

: 2.5 m

Height of stack(m)

: 100 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

2 30°C

Temperature of Stack Gases - Ts (°C)

: 75

Velocity of Stack Gases (m/sec.)

Flow rate of PM (LPM)

7.15

Flow rate of Gas (LPM)

26

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Sulphur Dioxide (SO2)	IS: 11255(P-2): 1985, RA.2019	403.63	mg/Nm3	950.0
2	Acid Mist (H2SO4)	USEPA 8, 1983	35.66	ma/Nm3	50.0

End of Report

"Experience the unimpginable"



Checked by





Page No. 1/1

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

9 SC-40, 3rd Floor, Narayan Vihar S. Ajmer Road, Jaipur Raj. 302020 9929108691, 9810205356, 8005707098, 9549956601

£ 0141-2954638

SII bd@vibranttechnolab.com www.vibranttechnolab.com





Sample Number: VTL/S/013

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270013/A

Format No

: 7.8 F-03

Party Reference No : NIL

Report Date Period of Analysis : 27/03/2023-30/03/2023

: 30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

Lead Primary Plant With Bag House (SKS Furnace)

Sample Collected By

VTL Team

Date of Sampling

: 25/03/2023

Sampling duration (Minutes)

: 39 min. (11:00 to 11:39 hrs.)

Stack attached to

: Bag House

Make of stack Diameter of stack(m)

: Iron : 2.0 m

Height of stack(m)

: 75 m

Instrument calibration status

: Calibrated

Meteorological Condition Ambient Temperature - Ta (°C)

: Clear Sky

Temperature of Stack Gases - Ts (°C)

: 28°C : 63

Velocity of Stack Gases (m/sec.)

: 6.77

Flow rate of PM (LPM)

: 26

Flow rate of Gas (LPM)

Sampling condition

OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
Particulat	te Matter (PM)	IS: 11255 (P-1): 1985, RA 2019	30.06	mg/Nm3	50.0
Lead (Pb	Miles III- and a second and	USEPA-29:2017	3.21	10.800.000	10.0
BLQ≈ Below Lir	mit Of Quantification, "LOQ=		3.21	mg/Nm3	

End of Report



Checked by

ed Signatory



Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

V SC-40, 3rd Fibor, Narayan Vihar S, Atmer Road, Jaipur Raj. 302020 9929108691, 9810205256, 8005707098, 9549956601

T 0141-2954638

bd@vibranttechnolab.com www.vibranttechnolab.com





Sample Number: VTL/S/01

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba, District -

Rajpura Dariba Udaipur Rajasthan

: VTL/S/2303270001/A

Format No

: 7.8 F-03

Report No.

Party Reference No : NIL

Report Date

: 30/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023 : 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Lead Electro Refinery (Pyro) South Side

Sample Collected By

: VTL Team

Date of Sampling Sampling duration (Minutes)

: 25/03/2023 : 38 min. (10:25 to 11:03 hrs.)

Stack attached to

: Bag Filter : Iron

Make of stack Diameter of stack(m)

; 2 m

Height of stack(m)

: 40 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

: 25°C

Temperature of Stack Gases - Ts (°C) ; 125

Velocity of Stack Gases (m/sec.) Flow rate of PM (LPM)

: 7,94

Flow rate of Gas (LPM)

1 26

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA


S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Matter (PM)	IS: 11255 (P-1) : 1985, RA 2019	33.48	mg/Nm3	50.0
2	Lead (Pb)	USEPA-29:2017	3.70	mg/Nm3	10.0

*BLQ= Below Limit Of Quantification, **LOQ= Limit Of Quantification

End of Report



Checked by





Page No. 1/1

Approved 8 Certified EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Sample Number: VTL/S/02

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270002/A

Format No

7.8 F-03

Party Reference No : NIL Report Date

: 30/03/2023

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Lead Electro Refinery (Pyro) North Side

Sample Collected By

: 25/03/2023

Date of Sampling

: 40 min. (12:00 to 12:40 hrs.)

Sampling duration (Minutes) Stack attached to

: Bag Filter

Make of stack

: Iron

Diameter of stack(m)

Height of stack(m)

2 m

: 40 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

Temperature of Stack Gases - Ts (°C) Velocity of Stack Gases (m/sec.)

1 115

Flow rate of PM (LPM)

: 7.61

: 25

Flow rate of Gas (LPM)

Sampling condition

Protocol used

OK : IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019	27.56	mg/Nm3	50.0
2	Lead (Pb)	USEPA-29:2017	2.52	mg/Nm3	10.0

End of Report



Checked by





Page No. 1/1

Approved & Cantilled EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Sample Number : VTL/S/04

Name & Address of the Party : M/s Hindustan Zino Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270004/A

Format No

7.8 F-03

Report Date

Party Reference No : NIL

30/03/2023 Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: TGT Lead Plant

Sample Collected By

: VTL Team

Date of Sampling

: 24/03/2023

Sampling duration (Minutes)

: 27 min. (10:40 to 11:07 hrs.)

Stack attached to

: Blast Furnace, Acid Plant & CDT Input

Make of stack

: Iron

Diameter of stack(m)

: 2.0 m

Height of stack(m)

100 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

: 26°C

Temperature of Stack Gases - Ts (°C)

: 48

Velocity of Stack Gases (m/sec.)

: 20.82

Flow rate of PM (LPM)

: 37

Flow rate of Gas (LPM)

2.0

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Sulphur Dioxide (SO2)	IS: 11255(P-2): 1985, RA.2019	240.60	mg/Nm3	950.0
2	Acid Mist (H2SO4)	USEPA 8, 1983.	35.29	mg/Nm3	50.0

*BLQ= Below Limit Of Quantification, **LOQ= Limit Of Quantification

End of Report



Checked by





Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified





Sample Number :

VTL/S/05

Name & Address of the Party : M's Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270005/A

Format No

: 7.8 F-03

Party Reference No

Report Date

: 30/03/2023

Period of Analysis Receipt Date

: 27/03/2023-30/03/2023 : 27/03/2023

Sample Description

General Information:-

Sampling Location

Sample Collected By

Date of Sampling

Sampling duration (Minutes)

Stack attached to

Make of stack

Diameter of stack(m)

Height of stack(m)

Instrument calibration status

Meteorological Condition Ambient Temperature - Ta (°C)

Temperature of Stack Gases - Ts (°C)

Velocity of Stack Gases (m/sec.)

Flow rate of PM (LPM) Flow rate of Gas (LPM)

Sampling condition

Protocol used

: Stack Emission Monitoring

Led Secondary Plant With Bag House (Blast Furnace)

VTL Team

24/03/2023

31 min. (12:30 to 13:01 hrs.)

Bag Fifter

Iron

: 2.2 m

: 75 m : Calibrated

: Clear Sky

: 25°C

: 58

8.29

32

: OK

: IS 11255 & USEPA

No.	Parameters	Took Market		4	
15	Particulate Matter (PM)	Test Method	Results	Units	Limits
		IS: 11255 (P-1) ; 1985, RA 2019	36.11	mg/Nm3	50.0
Commence of	Lead (Pb)	USEPA-29:2017	2.00		30.0
LQ=	Below Limit Of Quantification, **LO	Dis Limit Of Overhisestics	3.82	mg/Nm3	10.0

End of Report



Yadav JAIPUR (a) Incharge athorized Signator



Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

9 SC-40, 3rd Figer, Narayan Vihar S, Ajmer Road, Jajpur Raj. 302020 9929108691, 9810205356, 8005707098, 9549958601

@ 0141-2954638

bd@vibranttechnclab.com www.vibranttechnolab.com





Sample Number: VTL/S/09

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Report No.

: VTL/S/2303270009/A

Format No

7.8 F-03 Party Reference No ; NIL

Report Date

: 30/03/2023

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

Rajpura Dariba Udaipur Rajasthan

General Information:-

Sampling Location

: Lead Electro Refinery lead Plant (M&C) North Side

Dariba Smelter Complex, Post- Dariba District -

Sample Collected By

: VTL Team

Date of Sampling

: 25/03/2023

Sampling duration (Minutes)

: 44 min. (13:00 to 13:44 hrs.)

Stack attached to

: Bag Filter

Make of stack

: Iron

Diameter of stack(m)

Height of stack(m)

: 2 m

: 40 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C)

: 30°C

Temperature of Stack Gases - Ts (°C)

Velocity of Stack Gases (m/sec.)

: 139 7.37

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

: 23

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019	32.19	mg/Nm3	50.0
2	Lead (Pb)	USEPA-29:2017	3.63	mg/Nm3	10.0

*BLQ= Below Limit Of Quantification, **LOQ= Limit Of Quantification

End of Report



Checked by

RK Yadav Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Colonica EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified





Sample Number: VTL/S/10

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270010/A

Format No

: 7.8 F-03

Party Reference No : NIL

Report Date

: 30/03/2023 Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Lead Electro Refinery lead Plant (M&C)

Sample Collected By

: VTL Team

Date of Sampling

: 25/03/2023

Sampling duration (Minutes)

: 43 min (16:00 to 16:43 hrs.)

Stack attached to

: Bag Filter

Make of stack Diameter of stack(m) : Iron

Height of stack(m)

: 2 m : 40 m

Instrument calibration status

: Calibrated

Meteorological Condition

: Clear Sky

Ambient Temperature - Ta (°C) Temperature of Stack Gases - Ts (°C)

: 27°C

Velocity of Stack Gases (m/sec.)

: 7.15

Flow rate of PM (LPM)

Flow rate of Gas (LPM)

: 23

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Matter (PM)	IS: 11255 (P-1): 1985, RA 2019	44.49	mg/Nm3	50.0
2	Lead (Pb)	USEPA-29 2017	3.41	mg/Nm3	10.0

BLQ= Below Limit Of Quantification, "LOQ= Limit Of Quantification

End of Report



Checked by





Page No. 1/1

Approved & Certified) EPA 1986 Recognised, ISO:9001 and OHSAS:45001 Certified







Sample Number: VTL/S/03

Name & Address of the Party : M's Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/S/2303270003/A

Format No Party Reference No : NIL

: 7.8 F-03

Report Date

: 30/03/2023

: 27/03/2023

Period of Analysis : 27/03/2023-30/03/2023 Receipt Date

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: Coal Crusher

Sample Collected By

: VTL Team

Date of Sampling

: 25/03/2023

Sampling duration (Minutes)

: 26 min. (16:10 to 16:36 hrs.)

Stack attached to

: Bag Filter

Make of stack

: Iron

Diameter of stack(m)

: 1.3 m

Height of stack(m)

: 30 m

Instrument calibration status

: Calibrated

Meteorological Condition

Ambient Temperature - Ta (°C)

: Clear Sty

Temperature of Stack Gases - Ts (°C)

: 29°C : 37

Velocity of Stack Gases (m/sec.) Flow rate of PM (LPM)

9.50

Flow rate of Gas (LPM)

: 39

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	Test Method	Results	Units	Limits
1	Particulate Matter (PM)	articulate Matter (PM) IS: \$1255 (P.A.) 4005 PA 4545		Gillia	Limits
*DI 0	Below Limit Of Quantification **! Or	IS: 11255 (P-1): 1985, RA 2019	38.67	mg/Nm3	50.0

: End of Report*



Checked by





Page No. 1/1

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

SC-40, 3rd Floor, Narayan Vihar S. Ajmer Road, Jaipur Raj. 302020





Sample Number: VTL/S/12

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba, District -

Rajpura Danba Udaipur Rajasthan

Report No.

: VTL/S/2303270012/A

Format No.

: 7.8 F-03

Party Reference No : NIL Report Date

Period of Analysis ; 27/03/2023-30/03/2023

: 30/03/2023

Receipt Date

: 27/03/2023

Sample Description

: Stack Emission Monitoring

General Information:-

Sampling Location

: CPP 2X85 MW

Sample Collected By

: VTL Team

Date of Sampling

: 24/03/2023

Sampling duration (Minutes)

: 18 min. (15:30 to 15:48 hrs.)

Stack attached to

: ESP

Make of stack Diameter of stack(m)

: Iron

Height of stack(m)

4.0 m

Instrument calibration status

: 165 m

Meteorological Condition

: Calibrated

: Clear Sky

Ambient Temperature - Ta (°C)

: 32°C

Temperature of Stack Gases - Ts (°C) : 120 Velocity of Stack Gases (m/sec.)

Flow rate of PM (LPM)

: 17.06 : 55

Flow rate of Gas (LPM)

2.0

Sampling condition

: OK

Protocol used

: IS 11255 & USEPA

S.No.	Parameters	**************************************	1		
1	Particulate Matter (PM)	adjourner Melly (The		Units	Limits
_	The Control of the Co	IS: 11255 (P-1) : 1985, RA 2019	33.14	mg/Nm3	50
-	Sulphur Dioxide (SO2)	IS: 11255(P-2): 1985, RA 2019	1083.0		W-720
3	Oxide of Nitrogen (NO2)	IS-11255 (P-7), RA 2017	ANDRES	mg/Nm3	600
	Mercury (Hg)	TOTAL OF CONTROL STATE OF THE S	395.5	mg/Nm3	300
BLQ=	Below Limit Of Quantification, **LOG	USEPA 29: 1996	0.021	mg/Nm3	0.03
	TOC	x= Limit Of Quantification			0.00

End of Report







RK Yadavi Lab Incharge Authorized Signatory



Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

HINDUSTAN ZINC LIMITED RAJPURA DARIBA MINE

Average Ambient Air Quality Monitoring Results

Oct - 22

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (µg/m3)
Near Laboratory	72.79	29.60	11.25	3.83	370
Near DG Set	66.92	29.50	12.20	3.37	370
Near AB - Type Quarter	64.36	27.06	13.48	3.21	350

Nov - 22

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (μg/m3)
Near Laboratory	74.02	36.92	14.24	5.46	290
Near DG Set	79.01	40.44	13.32	3.43	350
Near AB - Type Quarter	70.14	34.11	12.45	4.09	310

Dec - 22

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (μg/m3)
Near Laboratory	67.13	29.14	12.52	5.59	390
Near DG Set	73.88	32.22	12.34	5.51	410
Near AB - Type Quarter	69.98	34.57	12.77	5.17	340

Jan - 23

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (μg/m3)
Near Laboratory	74.25	34.18	14.16	4.51	340
Near DG Set	68.15	29.53	14.90	5.08	380
Near AB - Type Quarter	65.66	30.86	13.82	6.28	310

Feb - 23

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (µg/m3)
Near Laboratory	81.53	42.65	12.53	3.96	380
Near DG Set	73.05	31.86	12.47	4.04	360
Near AB - Type Quarter	80.61	37.48	14.34	6.55	340

Mar - 23

Name of Monitoring Station	PM 10 (μg/m3)	PM 2.5 (μg/m3)	NO2 (μg/m3)	SO2 (μg/m3)	CO (μg/m3)
Near Laboratory	83.10	35.02	12.67	6.26	330
Near DG Set	80.26	31.84	12.54	3.87	320
Near AB - Type Quarter	76.40	35.20	12.87	6.60	290

(Apury Gautam)

Team Member - Environment Rajpura Dariba Mines 17

Issue Date: 31/12/2022

Office & Entertainty - 2247 - Size Side of G. T. Rosti Lindsico (nocental Area Ghazathan - 201 office) destruction with a Confederal Confederal Confederal Research (notation of employments) and comprehensive community of the Confederal Confed

TEST REPORT

Ambient Air Quality Monitoring

Test Report No.: EKO/040/27/1222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Sampling Location

Sampling Time

Sampling Plan & Procedure

Analysis Duration

Ambient Temperature ("C")
Average Flow Rate of SPM (m³/min.)
Average Flow Rate of Gases (lpm)

Weather Conditions Remark (if any) : Ambient Air

: 22/12/2022 To 23/12/2022 : EPEPL (Mr. Umesh Kumar)

: 27/12/2022

: Near Storm Water Pond (North West)

: 24.0 Hrs.

: SOP-AAQ/15

: 27/12/2022 To 31/12/2022

: 17.0 : 1.15

1.0 Clear

: NA

RESULTS

NEGOE 10					
S. No.	Parameters	Test Methods	Results	Units	Limits as per CPCB Notification, 18th Nov 2009
1	Particulate Matter (PM10)	IS: 5182 (P-23)	80.4	µg/m³	100.0
2	Particulate Matter (PM2.5)	EK0/CHEM/SOP/AAQ-01	49.6	µg/m³	60.0
3	Sulphur Dioxide (as SO ₂)	IS: 5182 (P-2)	25.2	µg/m³	80.0
4	Nitrogen Dioxide (as NO ₂)	IS: 5182 (P-6)	45.9	μg/m³	80.0
5	Carbon Monoxide (as CO)	IS: 5182 (P-10)	1.17	mg/m ³	4.0
6	Lead (as Pb)	IS: 5182 (P-22)	<0.1	µg/m³	1.0
7	Nickel (as NI)	EKO/CHEM/SOP/AAQ-02	<15.0	ng/m ³	20.0
8	Arsenic (as As)	EK0/CHEM/SOP/AAQ-02	<5.0	ng/m³	6.0
9	Ozone (as O ₃)	IS: 5182 (P-9)	<10.0	µg/m³	180.0
10	Ammonia (as NH ₃)	APHA Method 401	<20.0	µg/m³	400.0
11	Benzene (as C ₆ H ₆)	IS: 5182 (P-11)	<1.0	µg/m°	5.0
12	Benzo(alpha) Pyrine-Particulate Phase Only	IS: 5182 (P-12)	<1.0	ng/m³	1.0

Notes

- The results given above are related to the tested sample, for various parameters, as observed at the time of at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.

The test report will not be used for any publicity/legal purpose.

4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer Sample received for biological tests will be destroyed after 7 days from the date of issue of test report.

Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT, LTD.
PURNIMA GRADHAN
TECHNICAL MANAGER
(Authorised Signatory)

Page 1 of 1



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certifled Company).

TEST REPORT

Ambient Air Quality Monitoring

Test Report No.: EKO/041/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-(Rajasthan)

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Sampling Location

Sampling Time

Sampling Plan & Procedure

Analysis Duration

Ambient Temperature (°C) Average Flow Rate of SPM (m3/min.)

Average Flow Rate of Gases (Ipm) Weather Conditions

Remark (if any)

: Ambient Air

22/12/2022 To 23/12/2022

EPEPL (Mr.Umesh kumar) 27/12/2022

Near Main Gate (South)

24.0 Hrs.

SOP-AAQ/15

27/12/2022 To 31/12/2022

17.0 1.12

: 1.0 : Clear

: NA

RESULTS

S. No.	Parameters	Test Methods	Results	Units	Limits as per CPCB Notification, 18th Nov 2009
1	Particulate Matter (PM10)	IS: 5182 (P-23)	72.9	µg/m³	100.0
2	Particulate Matter (PM2.5)	EK0/CHEM/SOP/AAQ-01	42.8	µg/m³	60.0
3	Sulphur Dioxide (as SO ₂)	IS: 5182 (P-2)	26.9	hã/m,	80.0
4	Nitrogen Dioxide (as NO ₂)	IS: 5182 (P-6)	32.5	µg/m³	80.0
5	Carbon Monoxide (as CO)	IS: 5182 (P-10)	1.16	mg/m ³	4.0
6	Lead (as Pb)	IS: 5182 (P-22)	<0.1	µg/m³	1.0
7	Nickel (as Ni)	EK0/CHEM/SOP/AAQ-02	<15.0	ng/m³	20.0
8	Arsenic (as As)	EK0/CHEM/SOP/AAQ-02	<5.0	ng/m³	6.0
9	Ozone (as O ₃)	IS: 5182 (P-9)	<10.0	µg/m³	180.0
10	Ammonia (as NH ₃)	APHA Method 401	<20.0	µg/m³	400.0
11	Benzene (as C ₆ H ₆)	IS: 5182 (P-11)	<1.0	µg/m³	5.0
12	Benzo(alpha) Pyrine-Particulate Phase Only	IS: 5182 (P-12)	<1.0	ng/m³	1.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer. Sample received for biological tests will be destroyed after 7 days from the date of issue of test report.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

For EKO PRO ENGINEERS PVT LTD - PURNIMA CHAUGAN **FECHNICALIMANAGER** (Authorised Signatory)



EKO PAO ENGINEERS PVT.

Environmental Consultants and Analytical Laboratory (An ISO 9981:2015 Certified Company)

TEST REPORT

Ambient Air Quality Monitoring

Test Report No. ; EKO/042/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur (Rajasthan)

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on Sampling Location

Sampling Time

Sampling Plan & Procedure

Analysis Duration

Ambient Temperature (°C)

Average Flow Rate of SPM (m3/min.) Average Flow Rate of Gases (lpm)

Weather Conditions Remark (if anv)

: Ambient Air

23/12/2022 To 24/12/2022

EPEPL (Mr. Umesh Kumar) 27/12/2022

Near SLF Area 24.0 Hrs.

SOP-AAQ/15

27/12/2022 To 31/12/2022

17.0 : 1.14

1.0 : Clear : NA

RESULTS

S. No.	Parameters	Test Methods	Results	Units	Limits as per CPCB Notification, 18th Nov 2009
1	Particulate Matter (PM10)	IS: 5182 (P-23)	89.1	µg/m³	100.0
2	Particulate Matter (PM2.5)	EK0/CHEM/SOP/AAQ-01	52.8	µg/m³	60.0
3	Sulphur Dioxide (as SO ₂)	IS: 5182 (P-2)	22.4	ug/m³	80.0
4	Nitrogen Dioxide (as NO ₂)	IS: 5182 (P-6)	36.9	µg/m³	80.0
5	Carbon Monoxide (as CO)	IS: 5182 (P-10)	1.24	mg/m ³	4.0
6	Lead (as Pb)	IS: 5182 (P-22)	<0.1	µg/m³	1.0
7	Nickel (as Ni)	EK0/CHEM/SOP/AAQ-02	<15.0	ng/m³	20.0
8	Arsenic (as As)	EK0/CHEM/SOP/AAQ-02	<5.0	ng/m³	6.0
9	Ozone (as O ₃)	IS: 5182 (P-9)	<10.0	µg/m³	180.0
10	Ammonia (as NH ₃)	APHA Method 401	<20.0	µg/m³	400.0
11	Benzene (as C ₆ H ₆)	IS; 5182 (P-11)	<1.0	µg/m³	5.0
12	Benzo(alpha) Pyrine-Particulate Phase Only	IS: 5182 (P-12)	<1.0	ng/m ³	1.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer Sample received for biological tests will be destroyed after 7 days from the date of issue of test report.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT. LTD. PURNIMA CHAUHAN TECHNICAL MANAGER (Authorised Signatory)



EKO PAO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 Certified Company)

TEST REPORT

Ambient Air Quality Monitoring

Test Report No.: EKO/043/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura dariba Mines

Udaipur (Rajasthan)

Sample Description

Sample Drawn on

Sample Drawn by

Sample Received on

Sampling Location

Sampling Time

Sampling Plan & Procedure

Analysis Duration Ambient Temperature (°C)

Average Flow Rate of SPM (m3/min.) Average Flow Rate of Gases (lpm)

Weather Conditions Remark (if any)

Ambient Air

23/12/2022 To 24/12/2022

EPEPL (Mr.Umesh Kumar) : 27/12/2022

: Near CPP Area (North East)

: 24.0 Hrs. : SOP-AAQ/15

: 27/12/2022 To 31/12/2022

: 17.0 1.15

: 1.0 : Clear : NA

RESULTS

S. No.	Parameters	Test Methods	Results	Units	Limits as per CPCB Notification, 18th Nov 2009
1	Particulate Matter (PM10)	IS: 5182 (P-23)	81.6	µg/m³	100.0
2	Particulate Matter (PM2.5)	EK0/CHEM/SOP/AAQ-01	50.9	µg/m ³	60.0
3	Sulphur Dioxide (as SO ₂)	IS: 5182 (P-2)	20.5	µg/m³	80.0
4	Nitrogen Dioxide (as NO ₂)	IS: 5182 (P-6)	35.9	µg/m³	80.0
5	Carbon Monoxide (as CO)	IS: 5182 (P-10)	1.24	mg/m ³	4.0
6	Lead (as Pb)	IS: 5182 (P-22)	<0.1	µg/m³	1.0
7	Nickel (as Ni)	EK0/CHEM/SOP/AAQ-02	<15.0	ng/m³	20.0
8	Arsenic (as As)	EK0/CHEM/SOP/AAQ-02	<5.0	ng/m³	6.0
9	Ozone (as O ₃)	IS: 5182 (P-9)	<10.0	µg/m³	180.0
10	Ammonía (as NH ₃)	APHA Method 401	<20.0	µg/m³	400.0
11	Benzene (as C ₆ H ₆)	IS: 5182 (P-11)	<1.0	µg/m³	5.0
12	Benzo(alpha) Pyrine-Particulate Phase Only	IS: 5182 (P-12)	<1,0	ng/m³	1.0

Notes:

- 1. The results given above are related to the tested sample, for various parameters, as observed at the time of at the time of Sampling. The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer. Sample received for biological tests will be destroyed after 7 days from the date of issue of test report.
- 5. Responsibility of the Laboratory is limited to the invoiced amount only.

** End of Report **

FOR EKO PRO ENGINEERS PVT. LTD. PURNIMA GHANHAN TECHNICAL MANAGER (Authorised Signatory)







Sample Number: VTL/AA/01

M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba, District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/A/2303270001/A

Format No.

: 7.8 F-02

Party Reference No : NIL

Report Date

: 30/03/2023 : 27/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Sample Description

Name & Address of the Party

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Sample Collected By

Sampling Equipment used

Instrument Code

Coordinates Meteorological condition during monitoring

Date of Monitoring

Time of Monitoring

Ambient Temperature (°C)

Surrounding Activity Scope of Monitoring

Method of Sampling Sampling Duration

Parameter Required

Near Storm Water Pond (North - West)

VTL Team

: RDS/FPS

: VTL/RDS/FPS/01

: Clear Sky

: 22/03/2023 To 23/03/2023

: 15:00 to 15:00 Hrs.

: Min:18" Max 31"

: Human, Vehicular & Plant Act.

: Regulatory Requirment

: IS:5182

: 24 Hrs.

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1	Particulate Matter (as PM10)	(S:5182 (P- 23)-2006, RA. 2017	77.27	µg/m³	100
2	Particulate Matter (as PM2.5)	IS:5182 (P- 24)-2019	30,77	µg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA:2018	17.13	hð/m³	80
4	Sulphur Dioxide (as SO2)	IS:5182 (P-2)-2001, RA. 2018	8.36	hð/m³	80
5	Lead (as Pb)	IS 5182 (P-22) : 2004, RA 2019	0.11	µg/m³	7
6	Arsenic (as As)	Methods of air sampling and analysis.3rd ed., 1988, Method No.302	*BLQ (**LOQ 0.15)	ng/m³	6
7	Nickel (as Ni)		*BEQ (**LOQ 5.0)	ng/m²	20
8	Ammonia (as NH3)	Methods of air sampling and analysis,3rd ed.,1988, Method No. 401	13.19	µg/m³	400
9	Benzene (as C6H6)	IS 5182 (P-11)-2006, RA.2017	*BLQ (**LOQ 1.0)	µg/m³	5
10	Benzo (alpha) Pyrene-Particulate Phase Only	IS:5182 (P-12):2004, RA:2019	*BLQ (**LOQ 0.2)	ng/m³	1



Checked by

JAIPUR at Acharge Authorized Signatory



Page No. 1/2 g

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

T 0141-2954638

9929108691 9810205356 8005707098 9549956501





Sample Number: VTL/AA/01

Report No.

: VTL/A/2303270001/A

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
11	Ozone (as O3)	IS 5182 (P-9):1974, RA.2019	9.3	µg/m³	180

BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report

"Experience the unimaginable"



Checked by





Page No. 2/2

- V SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020
- 9929108691, 9810205356, 8005707098, 9549956601



Sample Number: VTL/AA/01

M/s Hindustan Zinc Ltd.

Report No.

: VTL/A/2303270001/B

Dariba Smelter Complex, Post- Dariba District -

Format No. Party Reference No : NIL

: 7.8 F-02

Report Date

: 30/03/2023

Rajpura Dariba Udaipur Rajasthan

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sample Description

Name & Address of the Party

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Sample Collected By

: VTL Team

Sampling Equipment used

: ROS/FPS

Instrument Code

: VTL/RDS/FPS/01

Coordinates

Meteorological condition during monitoring

Clear Sky

Date of Monitoring

22/03/2023 To 23/03/2023

: Near Storm Water Pond (North - West)

Time of Monitoring

15:00 to 15:00 Hrs.

Ambient Temperature (°C)

Min.18° Max 31°

Surrounding Activity

Scope of Monitoring

Human, Vehicular & Plant Act.

Regulatory Requirment

Method of Sampling Sampling Duration

: IS:5182

: 24 Hrs.

Parameter Required

As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1 Car	bon Monoxide (as CO)	Lab SOP no. VTL/STP/02:2022, STP-08	0.63	mg/m³	4

"BLQ-Below Limit Of Quantification, ""LOQ-Limit Of Quantification.

***End of Report**



Checked by

JAIPUR

BK Yadav

Incharge Authorized Signatory

Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

9 SC-40, 3rd Floor, Narayan Vihar S. Ajmer Road, Jaipur Raj. 302020

_ 9929108691, 9810205356, 8005707098, 9549956601

£ 0141-2954638

bd@vlbranttechnolab.com www.whranttschoolsh.com





Sample Number: VTL/AA/02

Sample Description

M/s Hindustan Zinc Ltd.

Report No.

: VTL/A/2303270002/A

Dariba Smelter Complex, Post- Dariba District -

Format No

: 7.8 F-02

: 30/03/2023

: 27/03/2023

Rajpura Dariba Udaipur Rajasthan

Party Reference No : NIL

Report Date

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Name & Address of the Party :

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

: Near Main Gate (South)

Sample Collected By

: VTL Team

Sampling Equipment used

: Combo Samplor

Instrument Code

: VTL/Combo/01

Coordinates

Meteorological condition during monitoring

: Clear Sky

Date of Monitoring

: 22/03/2023 To 23/03/2023

Time of Monitoring

: 15:30 to 15:30 Hrs.

Ambient Temperature (°C)

: Min.18" Max 31"

Surrounding Activity

: Human, Vehicular & Plant Act.

Scope of Monitoring

: Regulatory Requirment

Method of Sampling

; IS:5182

Sampling Duration

: 24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1	Particulate Matter (as PM10)	IS:5182 (P- 23)-2006, RA. 2017	83.27	µg/m³	100
2	Particulate Matter (as PM2.5)	IS:5182 (P- 24)-2019	38.49	μg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA 2018	19.65	µg/m²	80
4	Sulphur Dioxide (as SO2)	IS:5182 (P-2)-2001, RA. 2018	10.79	µg/m³	80
5	Lead (as Pb)	IS 5182 (P-22) : 2004, RA.2019	0.10	µg/m³	.5
6	Arsenic (as As)	Methods of air sampling and analysis.3rd ed.,1988, Method No.302	*BLQ (**LOQ 0,15)	ng/m³	6
7	Nickel (as Ni)	USEPA compendium (O-3 2, 1999	*BLQ (**LOQ 5.0)	ng/m³	20
8	Benzene (as C6H6)	IS 5182 (P-11)-2006, RA.2017	*BLQ (**LOQ 1.0)	µg/m³	5
9	Benzo (alpha) Pyrene-Particulate Phase Only	I\$:5182 (P-12):2004, RA:2019	*BLQ (**LOQ 0.2)	ng/m³	1
10	Ammonia (as NH3)	Methods of air sampling and analysis,3rd ed.,1988, Method No. 401	14.33	µg/m³	400



Checked by

JAIPUR Lab Incharge Authorized Signatory



Page No. 1/2





Sample Number: VTL/AA/02

Report No.

: VTUA/2303270002/A

S.No	Parameters	T	T		
11	Ozone (as O3)	Test Method	Results	Results Units	NAAQS 2009
DI O	A CONTRACTOR OF THE PROPERTY O	IS 5182 (P-9):1974, RA.2019	10.6		G. Carriera Control
*BLQ	Below Limit Of Quantification, **LOC	2-Limit Of Quantification	(A)	Pym	180

End of Report

"Experience the unimaginable"



Checked by





Page No. 2/2

- 9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj, 302020
- 9929108691, 9810205356, 8005707098, 9549956601





Sample Number: VTL/AA/02

M/s Hindustan Zinc Ltd.

Report No.

: VTL/A/2303270002/B

Dariba Smelter Complex, Post- Dariba District -

Format No Party Reference No : NIL

: 7.8 F-02

Rajpura Dariba Udaipur Rajasthan

Report Date

: 30/03/2023

: 27/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Name & Address of the Party :

: Near Main Gate (South)

Sample Collected By

: VTL Team

Sampling Equipment used

: Combo Samplor

Instrument Code

: VTL/Combo/01

Coordinates

Meteorological condition during monitoring

Clear Sky

Date of Monitoring

: 22/03/2023 To 23/03/2023

Time of Monitoring

: 15:30 to 15:30 Hrs.

Ambient Temperature (°C)

Surrounding Activity

: Min.18" Max 31"

: Human, Vehicular & Plant Act.

Scope of Monitoring

: Regulatory Requirment

Method of Sampling

: IS:5182

Sampling Duration

24 Hrs.

Parameter Required

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1	Carbon Monoxide (as CO)	Lab SOP no. VTL/STP/02:2022, STP-08	0.66	mg/m³	4

BLQ-Below Limit Of Quantification, "LOQ-Limit Of Quantification

End of Report



Checked by



Page No. 1/1





Sample Number :

VTL/AA/03

M/s Hindustan Zinc Ltd.

Danba Smelter Complex, Post- Danba District -

Rajpura Dariba Udaipur Rajasthan

Name & Address of the Party :

Report No.

: VTL/A/2303270003/A

Format No

· 7.8 F-02

Party Reference No : NIL Report Date

: 30/03/2023

: 27/03/2023

Period of Analysis : 27/03/2023-30/03/2023 Receipt Date

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Sample Collected By

Sampling Equipment used

Instrument Code

Coordinates

Meteorological condition during monitoring

Date of Monitoring

Time of Monitoring

Ambient Temperature (°C)

Surrounding Activity

Scope of Monitoring

Method of Sampling Sampling Duration

Parameter Required

: Near SLF Area

VTL Team

RDS/FPS

: VTL/RDS/FPS/01

: Clear Sky

: 23/03/2023 To 24/03/2023

: 15:30 to 15:30 Hrs.

: Min.19° Max 33°

: Human, Vehicular & Plant Act,

: Regulatory Requirment

: IS:5182

: 24 Hrs.

: As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1	Particulate Matter (as PM10)	IS:5182 (P- 23)-2006, RA, 2017	75.69	µg/m³	100
2	Particulate Matter (as PM2.5)	IS:5182 (P- 24)-2019	27.85	μg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P-6)-2006, RA:2018	15.95	µg/m²	80
4	Sulphur Dioxide (as SO2)	IS:5182 (P-2)-2001, RA. 2018	7.88	hð/m³	80
5	Lead (as Pb)	IS 5182 (P-22) : 2004, RA 2019	0.09	µg/m³	1
6	Arsenic (as As)	Methods of air sampling and analysis,3rd ed.,1988, Method No.302	*BLQ (**LOQ 0.15)	ng/m³	6
7	Nickel (as Ni)	USEPA compendium IO-3 2,1999	*BLQ (**LOQ - 5.0)	ng/m³	20
В	Benzene (as C6H6)	IS 5182 (P-11)-2006, RA,2017	*BLQ (**LOQ 1.0)	µg/m³	5.
9	Benzo (alpha) Pyrene-Particulate Phase Only	IS:5182 (P-12):2004, RA.2019	*BLQ (**LOQ 0.2)	ng/m³	1.
10	Ammonia (as NH3)	Methods of air sampling and analysis, 3rd ed., 1988, Method No. 401	12,01	hā/w _a	400



Checked by





Page No. 1/2

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified





Sample Number: VTL/AA/03

Report No.

: VTL/A/2303270003/A

S.No.	Parameters	Test Method	Danist.		
11	Ozone (as O3)		Results	Units	NAAQS 2009
BLO.E	elow Limit Of Quantification, **LOC	IS 5182 (P-9):1974, RA,2019	8.7	µg/m²	180

""End of Report""



Checked by





Page No. 2/2

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

- 9 SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaiour Raj. 302020
- 9929108691,9810205356,8005707098,9549956601

3 0141-2954638

🖾 bd@vibranttechnolab.com www.vibrantfechnolab.com



Sample Number :

Sample Description

VTL/AA/03

M/s Hindustan Zinc Ltd.

Report No.

: VTL/A/2303270003/B

Dariba Smelter Complex, Post- Dariba, District -

Format No

: 7.8 F-02

Rajpura Dariba Udaipur Rajasthan

Party Reference No : NIL Report Date

: 30/03/2023

: 27/03/2023

Period of Analysis Receipt Date

: 27/03/2023-30/03/2023

: AMBIENT AIR QUALITY MONITORING

General Information:-

Name & Address of the Party

Sampling Location

Sample Collected By

Sampling Equipment used

Instrument Code

Coordinates

Meteorological condition during monitoring

Date of Monitoring

Time of Monitoring

Ambient Temperature (°C)

Surrounding Activity

Scope of Monitoring

Method of Sampling Sampling Duration

Parameter Required

Near SLF Area VTL Team

: RDS/FPS

: VTL/RDS/FPS/01

: Clear Sky

: 23/03/2023 To 24/03/2023

: 15:30 to 15:30 Hrs.

: Min.19° Max 33°

: Human, Vehicular & Plant Act.

: Regulatory Requirment

: IS:5182

: 24 Hrs.

As per work order

S.No.	Parameters	Control of the Contro	200		
		Test Method	Results	Units	NAAQS 2009
5	Carbon Monoxide (as CO)	Lab SOP no. VTL/STP/02:2022, STP-08	0.50		11/1/190 2003
BI O-F	Below Limit Of Quantification **!		0.50	mg/m³	4

LOQ-Limit Of Quantification

End of Report

Checked by

Morized Signatory

the unimaginable"

Page No. 1/1

- SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jaipur Raj. 302020
- 9929108691, 9810205356, 8005707098, 9549956601

- S 0141-2954638
- bd@vibrenttechnolab.com
- www.vibranttechnolab.com





Sample Number: VTL/AA/04

M/s Hindustan Zinc Ltd.

Report No.

; VTL/A/2303270004/A

Format No

7.8 F-02

Dariba Smelter Complex, Post- Dariba District -Rajpura Dariba Udaipur Rajasthan

Party Reference No : NIL

Report Date

: 30/03/2023

: 27/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Sample Description

: AMBIENT AIR QUALITY MONITORING

General Information:-

Sampling Location

Near CPP (North East)

Sample Collected By

VTL Team

Sampling Equipment used

Combo Samplor

Instrument Code

: VTL/Combo/01

Coordinates

Name & Address of the Party

Meteorological condition during monitoring

Clear Sky

Date of Monitoring

23/03/2023 To 24/03/2023

Time of Monitoring

: 16:00 to 16:00 Hrs.

Ambient Temperature (°C)

Surrounding Activity

: Min. 191 Max 33°

: Human, Vehicular & Plant Act.

Scope of Monitoring Method of Sampling

: Regulatory Requirment : IS:5182

Sampling Duration

: 24 Hrs.


Parameter Required

As per work order

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
1	Particulate Matter (as PM10)	IS:5182 (P- 23)-2006, RA. 2017	74.99	μg/m³	100
2	Particulate Matter (as PM2.5)	IS:5182 (P- 24)-2019	28.51	µg/m³	60
3	Nitrogen Dioxide (as NO2)	IS:5182 (P- 6)-2006, RA 2018	17.06	µg/m³	80
4	Sulphur Dioxide (as SO2)	IS:5182 (P- 2)-2001, RA. 2018	9.08	µg/m²	80
5	Lead (as Pb)	IS 5182 (P-22) : 2004, RA.2019	0.09	µg/m³	1
6	Arsenic (as As)	Methods of air sampling and analysis,3rd ed.,1988, Method No,302	*BLQ (**LOQ 0.15)	ng/m³	- 6
7	Nickel (as Ni)	USEPA compendium IO-3.2,1999	*BLQ (**LOQ 5.0)	ng/m³	20
3	Benzene (as C6H6)	IS 5182 (P-11)-2006, RA 2017	*BLQ (**LOQ 1.0)	µg/m³	5
9	Benzo (alpha) Pyrene-Particulate Phase Only	IS:5182 (P-12):2004, RA:2019	*BLQ (**LOQ 0.2)	ng/m³	1
10	Ammonia (as NH3)	Methods of air sampling and analysis, 3rd ed., 1988. Method No. 401	11.80	µg/m³	400









Page No. 1/2

- © SC-40, 3rd Floor, Narayan Vihar S, Ajmer Road, Jalour Raj. 302020
- 9929108691, 9810205356, 8005707098, 9549955501





Sample Number: VTL/AA/04

Report No.

: VTL/A/2303270004/A

S.No.	Parameters	Test Method	Results	Units	NAAQS 2009
11 Ozon	e (as O3)	IS 5182 (P-9):1974, RA.2019	7.98	µg/m³	180

Q-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report

"Experience the unimaginable"



Checked by





Page No. 2/2

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

_ pagainesai 9810705356 8005707098 9549956601

C 0141-2954638

 bd@vibranttechnolab.com www.vibranttechnolab.com



Sample Number: VTL/AA/04

Mrs Hindustan Zinc Ltd.

Report No.

: VTL/A/2303270004/B

Dariba Smelter Complex, Post- Dariba District -

: Near CPP (North East)

: 23/03/2023 To 24/03/2023

: VTL Team

: Clear Sky

: Combo Samplor

: 16:00 to 16:00 Hrs.

: Min.19° Max 33°

: VTL/Combo/01

Format No

: 7.8 F-02 Party Reference No

Report Date

: 30/03/2023

1 27/03/2023

Receipt Date

Period of Analysis : 27/03/2023-30/03/2023

Sample Description

Name & Address of the Party

: AMBIENT AIR QUALITY MONITORING

Rajpura Dariba Udaipur Rajasthan

General Information:-

Sampling Location

Sample Collected By

Sampling Equipment used

Instrument Code

Coordinates

Meteorological condition during monitoring

Date of Monitoring Time of Monitoring

Ambient Temperature (°C) Surrounding Activity

Scope of Monitoring Method of Sampling

Sampling Duration Parameter Required

: Human, Vehicular & Plant Act. : Regulatory Requirment IS:5182

24 Hrs.

As per work order

S.No.	Parameters	Test Method	Results	10.00	
1	Carbon Monoxide (as CO)	Lab SOB as 1/THE PROPERTY.		Units	NAAQS 2009
	Relativities & O.C	Lab SOP no. VTL/STP/02:2022, STP-08	0.52	mg/m³	4

*BLQ-Below Limit Of Quantification, **LOQ-Limit Of Quantification

End of Report

Checked by

Lab ncharge Authorized Signator

Page No. 1/1

Approved & Certified EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified

9 SC-48, 3rd Floor, Narayan Vihar S. Ajmer Road, Jaipur Raj. 302020 9929108691, 9810205356, 8005707098, 9549956601

www.vibranttechnolab.com

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Ambient Air Quality Monitoring Report (Outside Plant)

(October'22-March'23)

Month	Parameters	Oct'22	Nov'22	Dec'22	Jan'23	Feb'23	Mar'23	
Village	rarameters							
	PM10	77.51	74.69	70.87	69.87	73.33	71.68	
	PM2.5	41.86	40.16	36.36	34.34	36.53	34.64	
Aanjana	SO2	9.58	11.23	10.53	9.46	9.63	8.93	
	NOx	10.63	11.56	11,32	10.44	10.62	9,941	
	Pb	BDL	BDL	BDL	BDL	BDL	BDL	
	PM10	67.14	70.48	69.77	58.31	66.82	63.96	
	PM2.5	36.17	39.00	38.37	26.17	33.82	31.03	
Makhanpuriya	SO2	7.48	8.822	8.315	7.21	6.622	6.685	
	NOx	8.102	9.468	9.822	8.61	7.085	6.96	
	Pb	BDL	BDL	BDL	BDL	BDL	BDL	
	PM10	79.32	77.12	73.3	75.46	78.28	75.72	
	PM2.5	43.19	41.34	38.91	41.96	39.29	36.78	
Mahenduriya	SO2	10.7	10.7	10.7	10,7	10.7	10.7	
	NOx	11.33	13.43	13.08	11.76	9.827	11.91	
	Pb	BDL	BDL	BDL	BDL	BDL	BDL	
	PM10	71.06	67.74	65.31	60.13	63.02	60.95	
	PM2.5	40.79	36.41	34.68	29.52	30.63	28,17	
Ladapacha	SO2	8.767	9.473	8.949	7,918	7.353	5.941	
THE SECOND TO SECOND TO SECOND	NOx	10.02	10.09	9.587	8.744	7.504	6.525	
	Pb	BDL	BDL	BDL	BDL	BDL	BDL	

Annexure IV (Cont.)

	PM10	78.57	76.47	75.62	72.57	79.61	76.28
	PM2.5	42.12	44.39	42.1	40.36	41.42	38.36
Lunera	SO2	9.782	10.03	9.677	10.568	8.834	7.869
	NOx	10.48	11.92	10.58	11.86	9.367	8.454
	Pb	BDL	BDL	BDL	BDL	BDL	BDL
	PM10	69,61	65.83	63.65	57.13	60.58	58.06
	PM2.5	38.91	34.74	32.54	24.17	28.99	26.41
Charana	SO2	8.582	9.313	7.683	6.581	6.39	5.815
	NOx	9.235	9.43	8.568	7.774	6.49	6.239
= =====================================	Pb	BDL	BDL	BDL	BDL	BDL	BDL
	PM10	80.45	79.52	77.2	81.04	83.77	79.98
	PM2.5	44.04	46.19	44.93	45.87	43.03	40.05
Kotadi	SO2	11.23	11.89	14.11	11.15	9.799	8.892
	NOx	12.48	12.53	15.17	12.02	10.02	9.955
_	Pb	BDL	BDL	BDL	BDL	BDL	BDL
	PM10	70.33	68.62	67.78	61.82	65.44	62.16
-	PM2.5	39.25	37.97	35.33	31.53	31.09	29.24
Chothpura	SO2	7.984	7,614	7.845	6.829	6.158	5,989
****	NOx	8.436	6.595	8.776	7.826	6.56	6.635
	Pb	BDL	BDL	BDL	BDL	BDL	BDL

^{*}All readings in ug/m³

(Vivek Kumar)

Head Environment

Dariba Smelter Complex

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Continuous Ambient Air Quality Monitoring Results

(October'22-March'23)

************		Prescribed			Me	Month		
Location		Limits*	Oct'22	Nov'22	Dec'22	Jan'23	Feb'23	Mar'23
	RSPM	100	71.05	71.98	74.51	67.25	64.71	67.53
Near to Main	SO2	80	35.78	35.12	34.64	14.87	5.96	9.12
Gate (South- West)	NOx	80	36.37	34.4	34.83	10.50	9.80	14.38
resty	CO	2	0.43	0.53	0.59	0.80	1.02	0.81
	RSPM	100	74.75	74.91	75.03	46.79	46.42	47.26
Near to SWP	SO2	80	36.02	34.9	34.84	12,42	12.28	5.43
(North-West)	NOx	80	35.61	34.52	35,20	8.57	11.94	9.12
	СО	2	0.50	0.97	1.05	0.93	1.06	0.54
	RSPM	100	75.65	77.77	71.86	55.29	63.43	56.38
Near to CPP	SO2	80	37.22	35.02	28.02	9.74	13.22	5.02
(North-East)	NOx	80	34.97	36.9	31.88	29.19	29.98	41.22
	CO	2	0.61	1.03	0.92	1.14	1.34	0.88
	RSPM	100	80.18	75.95	79.61	70.77	75.39	60.88
SLF (South-	SO2	80	29.7	17.27	26.11	12.25	13.74	10.31
East)	NOx	80	31.79	25.73	31.95	22.88	22.37	14.53
	СО	2	0.56	0.31	0.74	1.13	1.21	1.25

(Vivek Kumar)

Head Environment

Dariba Smelter Complex

^{*} National Ambient Air Standards, 2009

^{*} All readings in ug/m3, except CO in mg/m3

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Work Zone Environment Monitoring Results

(October'22-March'23)

Month Location	Parameters	Prescribed Standards*	Oct'22	Nov'22	Dec'22	Jan'23	Feb'23	Mar'23
			Zine	Plant				
Raw	SPM	10	8.59	9.00	8.04	9.24	9.14	9.05
Material Handling	SO ₂	5	0.142	0.159	0.156	0.142	0.169	0.113
(RMH)	Zn	5	0.896	1.145	0.924	1.254	1.070	1.00
Zinc Dust	SPM	10	6.19	7.16	5.52	5.25	7,45	7.03
Plant	SO ₂	5	0.061	0.078	0.048	0.053	0.072	0.068
riant	Zn	5	0.699	0.804	0.611	0.596	0.789	0.816
Purification Section	SPM	10	6.17	7.27	5.53	5.265	6.55	6.53
	SO ₂	5	0.065	0.084	0.053	0.057	0.076	0.074
	Zn	5	0.228	0.348	0.182	0.158	0.270	0.337
Las control and	SPM	10	2.32	2.41	2.41	2.05	2.99	2.29
Cell House	SO_2	5	0.196	0.204	0.184	0.164	0.201	0.156
	Zn	5	0.172	0.177	0.183	0.160	0.276	0.184
			Lead	Plant				
Raw	SPM	10	8.16	8.61	8.80	9.21	8.69	9.11
Material	SO ₂	5	0.123	0.127	0.089	0.108	0.109	0.097
Handling (RMH)	Pb	0.15	0.123	0.13	0.130	0.137	0.122	0.124
	SPM	10	7.01	7.23	7.74	8.00	8.06	7.88
SKS	SO ₂	5	0.149	0.153	0.100	0.133	0.121	0.109
	Pb	0.15	0.084	0.085	0.084	0.075	0.089	0.099
Blast	SPM	10	6.77	7.23	7.44	7.13	6.98	7.32
CONTROL CONTROL	SO ₂	5	0.092	0.108	0.104	0.090	0.091	0.085
Furnace	Pb	0.15	0.092	0.113	0.108	0.098	0.104	0.104
LEP	SPM	10	7.14	6.46	7.24	5.74	6.60	6.18
Melting &	SO ₂	5	0.065	0.072	0.079	0.060	0.083	0.062
Casting	Pb	0.15	0.070	0.059	0.095	0.055	0.067	0.064

^{*} Time Weighted Average (TWA) .All readings in ppm

(Vivek Kumar)

Head Environment Dariba Smelter Complex

^{*} Factory Act, 1948 (Schedule II)

Annexure VII

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Fugitive Emission Monitoring Results

(October'22-March'23)

Location	Parameters (All figures in μg/m³)
	TSPM
Prescribed Limit*	170)
Raw Material Handling (RMH) - Zinc	475.31
Roaster Plant	430.355
Calcine Handling	444.955
Coal Handling Plant (CPP)	417.89
Fly Ash Handling	440.72
Raw Material Handling (RMH) - Lead Plant	481.68
Near SKS Primary	419.01

Secondary fugitive emissions are monitored on 24 hrs basis at a distance of 10 m from the source.

(Vivek Kumar)

Head Environment

Dariba Smelter Complex

Issue Date: 31/12/2022



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9001:2015 SentRed Company)

Office & Laboratory 32/41 Sustin Side of G. T. Road, URBIDO Industrial Alexa, Ghazintaria - 201 009 (Biglin) NCR), NRSA, Chatter May 97 (11/80/10) 38 (07/80/87) 01/10/2010 77 (11/80/10) 48 (07/80/87) 01/10/2010 77 (11/80/10) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/87) 01/10/2010 77 (11/80/80) 48 (07/80/80) 48

TEST REPORT

Effluent Sample Analysis

Test Report No.: EKO/051/271222

Issued To

: HINDUSTAN ZINC LIMITED

Dariba Smelter Complex

Post - Dariba, District - Rajpura Dariba Mines

Udaipur-Rajasthan

Sample Description

: Effluent After Treatment (ETP Outlet)

Sample Drawn on

: 24/12/2022

Sample Drawn by

: EPEPL (Mr. Umesh kumar)

Sample Received on

: 27/12/2022

Sampling Location

From ETP Plant

Sampling Plan & Procedure

: SOP-W/66

Sample Quantity

301-11/00

our pic addring

: 2.0 Litre

Environmental Condition

: Normal

Analysis Duration

: 27/12/2022 To 31/12/2022

Remark (if any)

+ NA

RESULTS

S. No.	Parameters	Test Method	Results	Units	Limits as pe CTO
1	рН	IS: 3025 (P-11)	7.24		6.5-8.5
2	Total Suspended Solids	IS: 3025 (P-17)	40.0	mg/L	100.0
3	Oil & Grease	IS: 3025 (P-39)	<4.0	mg/L	10.0
4	COD (as O ₂)	IS: 3025 (P-58)	85.6	mg/L	250.0
5	BOD (@27°C for 3 days)	IS: 3025 (P-44)	18.0	mg/L	30.0
6	Sulphides (as S)	IS: 3025 (P-29)	<1.0	mg/L	2.0
7	Chloride (as Cl)	IS: 3025 (P-32)	510.7	mg/L	1000.0
8	Sulphate (as SO ₄)	IS: 3025 (P-24)	162.8	mg/L	1000.0
9	Fluoride (as F-)	IS: 3025 (P-60)	1.28	mg/L	2.0
10	Copper (as Cu)	EKO/CHEM/SOP-ICPMS/W-01	0.024	mg/L	1.0
11	Zinc (as Zn)	EKO/CHEM/SOP-ICPMS/W-01	0.62	mg/L	1.0
12	Cadmium (as Cd)	EKO/CHEM/SOP-ICPMS/W-01	< 0.001	mg/L	2.0
13	Chromium (as Cr+6)	IS: 3025 (P-52)	<0.05	mg/L	0.1
14	Chromium Total (as Cr)	EKO/CHEM/SOP-ICPMS/W-01	<0.005	mg/L	0.2
15	Lead (as Pb)	EKO/CHEM/SOP-ICPMS/W-01	0.016	mg/L	0.1
16	Phosphate Dissolved (as P)	IS: 3025 (P-31)	0.76	mg/L	5.0
17	Cyanide (as CN)	APHA 4500 CN K	Absent	mg/L	0.2
18	Nickel (as Ni)	EKO/CHEM/SOP-ICPMS/W-01	<0.005	mg/L	3.0
19	Iron (as Fe)	EKO/CHEM/SOP-ICPMS/W-01	0.31	mg/L	1.0
20	Free Available Chlorine	IS: 3025 (P-26)	<0.2	mg/L	0.5



Contact: +91 - 9818243870



EKO PRO ENGINEERS PVT. LTD.

Environmental Consultants and Analytical Laboratory (An ISO 9991-2915 Centified Company)

Office & Laboratory: 32/41, South Side of G. T. Road, UPSIDC Industrial Area, Ghazabad - 201 009 (Delhi-NCR) INDIA. Contact No. 9711159210, 9810249837, 9810249878 E-mail: email@exopro.in.ekuproangineers@gmail.com, wabsite: www.ekupro.in.

Test Report No.: EKO/051/271222

Issue Date: 31/12/2022

Notes:

- The results given above are related to the tested sample, as received & mentioned parameters.
 The customer asked for the above tests only.
- 2. This test report will not be generated again, either wholly or in part, without prior written permission of the Laboratory.
- 3. The test report will not be used for any publicity/legal purpose.
- 4. The test samples will be disposed off after 15 days from the date of issue of test report, unless until specified by the customer. Sample received for biological tests will be destroyed after 7 days from the date of issue of test report.
- Responsibility of the Laboratory is limited to the invoiced amount only.
 End of Report

FOR EKO PRO ENGINEERS PVT LTD.

PURHAMA CHAUNAN

TECHNICAL MANAGER

(Authorised Signetory)







Sample Number: VTL/WW/02

Sample Description

Sampling Location

Preservation

Sample Collected By

Method of sampling

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Danba Smelter Complex, Post- Dariba, District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTL/WW/2303270002/A

Format No Party Reference No : NIL

7.8 F-01

Report Date

: 30/03/2023

Period of Analysis : 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sampling Date

Sampling Type

: 24/03/2023 : Grab

Sample Quantity

: 2 Ltr.

: IS:3025

: Waste Water

: VTL Team

: ETP Plant (Outlet)

: Suitable Preservation

S.No.	Test Parameters	Result	Unit	Limits
1	рН	6.50		5.5 to 9.0
2	Total Suspended Solids (TSS)	1.80	mg/l	100
3	Oil & Grease	1.00	mg/l	10
4	Biochemical Oxygen Demand (BOD) (3 days @ 27°C)	5.70	mg/l	30
5	Chemical oxygen Demand (COD)	20.00	mg/l	250
6	Lead (as Pb)	*BLQ(**LOQ-0.1)	mg/l	0.1
7	Chromium (as Cr)	*BLQ(**LOQ-0.1)	mg/l	2
8	Copper (as Cu)	*BLQ(**LOQ-0.1)	mg/l	3
9	Zinc (as Zn)	0.44	mg/l	5
10	Nickel (as Ni)	*BLQ(**LOQ-0.1)	mg/l	3
11	Fluoride (as F)	0.83	mg/l	2
12	Sulphide (as S)	0.46	mg/l	2
13	Cadmium (as Cd)	*BLQ(**LOQ-0.1)	mg/l	2.0
14	Iron (as Fe)	0.33	mg/l	1:
15	Residual Free Chlorine	*BLQ(**LOQ-0.2)	mg/l	0.5

^{*}BLQ-Below Limit OF Quantification, **LOQ-Limit Of Detection E THE LIMIN BUILDING

End of Report



Checked by





Page No. 1/1

EPA 1986 Recognized, ISO:9001 and OHSAS:45001 Certified





Sample Number: VTL/VVV/02

Name & Address of the Party : M/s Hindustan Zinc Ltd.

Dariba Smelter Complex, Post- Dariba District -

Rajpura Dariba Udaipur Rajasthan

Report No.

: VTLWW/2303270002/B

Format No

: 7.8 F-01

Party Reference No : NIL

Report Date

: 30/03/2023

Period of Analysis ; 27/03/2023-30/03/2023

Receipt Date

: 27/03/2023

Sampling Date

: 24/03/2023

Sampling Type

Grab

Sample Quantity

: 2 Ltr.

Method of sampling

Preservation

Sample Description

Sampling Location

Sample Collected By

: IS :3025

: VTL Team

: Waste Water

: ETP Plant (Outlet)

: Suitable Preservation

S.No.	Test Parameters	Result	Unit	Limits
1	Hexavalant Chromium (Cr+6)	*BLQ(**LOQ-0.02)	mg/l	0.1
2	Chloride (as Cl)	79.33	mg/l	1000
3	Phosphate (as PO4)	0.24	mg/l	5
4	Sulphate (as SO4)	"BLQ(""LOQ-0.02)	mg/l	
5	Cyanide (as CN)	*BLQ(**LOQ-0.02)	mg/l	0.2

^{*}BLQ-Below Limit OF Quantification, **LOQ- Limit Of Detection

End of Report



Checked by

athorized Signatory

Page No. 1/1

- 9 SC-40, 3rd Floor, Narayan Vinar S. Ajmer Road, Jaipur Raj. 302020
- 9929108691, 9810205256, 8005707098, 9549956601

ANNEXURE - IX

Piezometer water Quality

Dec - 22 (Tailing dam)

(A11+	figures	in	nnm	exce	nt i	nH)	
177111	124163	411.	Digita.	CHECK	24	N 87	

Parameter	PW 1	PW 2	PW 3	PW 4	PW 5	PW 6
рН	7.36	7.51	7.59	7.85	7.44	7.92
Suspended Solids	18	23	13	10	21	8
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zine	BDL(<0.01)	BDL(<0.01)	0.06	0.11	BDL(<0.01)	0.29
Copper	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Iron	0.09	0.09	0.05	BDL(<0.01)	0.09	BDL(<0.01)
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	0.02	0.02	BDL(<0.01)	BDL(<0.01)	0.02	BDL(<0.01)
Cobalt	BDL(<0.01)	0.01	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)

Mar - 23 (Tailing dam)

(All figures in ppm except pH)

			The same and the	AND DESCRIPTION OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUM	
PW 1	PW 2	PW 3	PW 4	PW 5	PW 6
7.27	7.54	7.37	7.09	7.60	7.53
17	28	16	29	25	16
BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
0.04	0.07	0.07	0.05	0.04	0.04
BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
0.10	0.13	0.10	0.08	0.10	0.08
BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
the state of the s	0.02	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
The second secon	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)	BDL(<0,01)	BDL(<0.01)
	7.27 17 BDL(<0.01) 0.04 BDL(<0.01)	7.27 7.54 17 28 BDL(<0.01) BDL(<0.01) 0.04 0.07 BDL(<0.01) BDL(<0.01) 0.10 0.13 BDL(<0.001) BDL(<0.001) BDL(<0.001) BDL(<0.001) 0.02	7.27 7.54 7.37 17 28 16 BDL(<0.01)	PW 1 PW 2 PW 3 PW 4 7.27 7.54 7.37 7.09 17 28 16 29 BDL(<0.01)	7.27 7.54 7.37 7.09 7.60 17 28 16 29 25 BDL(<0.01)

Annexure X

Process water Quality results

Oct - 22

Parameter	Mine Water	Tailing Dam Water	Garland Drain Water
рН	7.06	7.14	7.29
Suspended Solids	22	21	26
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zinc	0.94	0.36	0.42
Copper	0.15	0.04	BDL(<0.01)
Iron	0.14	0.10	0.07
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	0.21	0.03	0.04
Cobalt	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
			All Course in more avaged to

(All figures in ppm except pH)

Nov - 22

Mine Water	Tailing Dam Water	Garland Drain Water
Total California		7.47
	10.55 04.550	100000000000000000000000000000000000000
27	25	23
BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
1.38	0.41	0.30
0.04	0.12	0.06
0.03	0.16	0.15
BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
0.17	0.06	0.04
BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
	1.38 0.04 0.03 BDL(<0.001)	7.14 7.49 27 25 BDL(<0.01) BDL(<0.01) 1.38 0.41 0.04 0.12 0.03 0.16 BDL(<0.001) BDL(<0.001) 0.17 0.06

(All figures in ppm except pH)

Dec - 22

Parameter	Mine Water	Tailing Dam Water	Garland Drain Water
pН	7.29	7.10	7.08
Suspended Solids	31	27	26
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zinc	1.69	1.02	1.03
Copper	0.24	0.14	0.08
Iron	0.10	0.05	0.08
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	0.03	0.06	0.06
Cobalt	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)

(All figures in ppm except pH)

Jan-23

Parameter	Mine Water	Tailing Dam Water	Garland Drain Water
pH	7.07	7.07	7.19
Suspended Solids	22	28	30
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zinc	0.53	1.03	0.83
Copper	0.02	0.04	0.03
Iron	0.02	0.07	0.06
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	0.03	0.09	0.08
Cobalt	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)

(All figures in ppm except pH)

Feb-23

Parameter	Mine Water	Tailing Dam Water	Garland Drain Water
pH	7.07	7.34	7,52
Suspended Solids	26	25	31
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zinc	1.45	0.42	0.27
Copper	0.11	0.09	0.13
Iron	0.05	0.07	0.10
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	0.10	0.07	0.06
Cobalt	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)

(All figures in ppm except pH)

Mar - 23

Parameter	Mine Water	Tailing Dam Water	Garland Drain Water
pH	7.19	7.20	7.46
Suspended Solids	22	32	28
Lead	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)
Zinc	1.74	0.83	0.25
Copper	0.17	0.06	0.06
Iron	0.03	0.06	0.06
Cadmium	BDL(<0.001)	BDL(<0.001)	BDL(<0.001)
Nickel	BDL(<0.01)	0.03	0.02
Cobalt	BDL(<0.01)	BDL(<0.01)	BDL(<0.01)

(All figures in ppm except pH)

Annexure XI

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Ambient Noise Monitoring Report

(October'22-March'23)

Plant	DARIBA SMELTER COMPLE			X	
Location	Boundary Wall near	Near Gate	Boundary wall	Behind main	
Prescribed Standards* (70-75)	Plantation site (SW)	No.2 (SE)	of CPP (NE)	(NW)	
October'22-March'23	58.4-68.3	59.2-69.3	58.4-68.5	57.9-68.0	

(Vivek Kumar)

Head Environment

Dariba Smelter Complex

Annexure XII

Hindustan Zinc Limited Dariba Smelter Complex Dariba, Dist. Rajsamand, Rajasthan.

Average Sulphur and ash content in coal Monitoring Report (October'22-March'23)

Month	Average Sulphur content %	Average Ash
October-22	1.38	16.41
November-22	1.46	18.78
December-22	1.45	17.77
January-23	1.08	16.41
February-23	0.71	15.85
March-23	0.56	19.71
Charles and the Control of the Contr		

(K Kathiresan)

Head CPP

Dariba Smelter Complex

Annexure XIII

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Expenditure made in environmental control measures (2022-23)

		Total amount	
Sr. No.	Description	(Rs. in lakhs)	
1	Green Belt Development, Maintenance of old plantation & landscaping	172.18	
2	Environment Monitoring	187.07	
3	Storm water ponds operation and maintenance & Monsoon management	0.15	
4	Environmental training, awareness and publicity	1.96	
5	Hazardous Waste Management	2782.10	
6	O & M of Organic waste Convertor	0.00	
7	Environmental Audit	3.91	
8	Returns, fees for Award & CTO	29.18	
9	Pollution control measure	346.60	
	Grand Total	3523.15	

HINDUSTAN ZINC LIMITED DARIBA SMELTER COMPLEX

Funds earmarked towards environmental control measures (2023 -24)

		Total amount	
Sr. No.	Description	(Rs. in lakhs)	
1	Green Belt Development, Maintenance of old plantation & landscaping	719.20	
2	Environment Monitoring	179.80	
3	Storm water ponds operation and maintenance & Monsoon management	76.00	
4	Environmental training, awareness and publicity	29.30	
5	Hazardous Waste Management	2040.90	
6	O & M of Organic waste Convertor	3.00	
7	Environmental Audit & IMS	11.00	
8	Returns, fees for Award & CTO	187.00	
9	Pollution control measure	122.00	
	Grand Total	3368.20	