

HZL/DSC/ENV/ES/2025/2

Date 23.09.2025

To,

The Member Secretary
Rajasthan State Pollution Control Board
4, Institutional Area
Jhalana Doongri
Jaipur-302004

File No. OGM/M-54

Sub: Environmental Statement for the year 2024-25 for Lead Smelter, Dariba, Rajsamand.

Ref: Consent to Operate No: F(HDF)/Rajsamand(Railmagra)/6461(1)/2020-2021/4945-4947 dated 03.02.2021.


Sir,

With reference to above subject please find enclosed herewith the Environmental Statement for the financial year 2024-25 for Lead Smelter, Dariba, Rajsamand.

Thanking You,

For Hindustan Zinc Limited

Yours Faithfully



(Deep kumar Agarwal)
Deputy SBU Director
Dariba Smelter Complex

Cc:

1. Regional Officer, RSPCB
Old excise office building,
Kalalwati, Rajnagar, Rajsamand, Pin code : 313324
2. The Deputy Director (S)/ Scientist- C
Ministry of Environment Forests and Climate Changes,
Integrated Regional Office, A-209 & 218, Aranya Bhawan,
Jhalana Institutional area, Jaipur – 302004
3. O/C

**Hindustan Zinc Limited
Dariba Smelter Complex**



**ENVIRONMENTAL STATEMENT FOR LEAD SMELTER
(FINANCIAL YEAR ENDING MARCH 31ST 2025)**

PREPARED & SUBMITTED BY

**Lead Smelter
Dariba Smelter Complex
Hindustan Zinc Limited
P.O. - Dariba, District – Rajasmand
Rajasthan - 313211**

FORM-V

**Environmental Statement
for the financial year ending the 31st March 2025**

PART-A

- i) Name and address of the owner/occupier of the industry operation or process : Arun Misra
CEO
M/s. Hindustan Zinc Limited
Dariba Smelter Complex
Hindustan Zinc Limited,
P.O.- Dariba, Tehsil- Relmagra
Dist. - Rajsamand
Rajasthan – 313 211
- (ii) Industry category : Red/ Large
Primary – (STC Code) : AAACH7354KST006
Secondary- (SIC Code) : Not Applicable
- (iii) Production Capacity :
Lead Cathode/Ingot : 125,000 TPA
Lead alloy(Pb-Sb & Pb-Ca) : 50,000 TPA

By-Products (in TPA)

Sulphuric acid for Lead Smelter	:	1,32,000 TPA
Copper as Copper Concentrate/matte (equivalent metal) in Lead Smelter	:	900 TPA
Antimony as Antimony Concentrate (equivalent Metal)	:	850
Bismuth as Bismuth Concentrate (equivalent Metal)	:	16 TPA
Zinc Oxide Compound	:	20000 TPA
Lead Concentrate Oxide	:	5000 TPA
Anode Slime	:	4000 TPA
Silver	:	400 TPA
Year of Establishment	:	2011
(iv) Date of Last Environmental Statement Submitted	:	21.09.2024

PART -B

WATER AND RAW MATERIAL CONSUMPTION

(1) Water consumption (m3 /d)*

Boiler/Cooling	:	1674
Domestic	:	103
Industrial Process	:	303

* Daily water consumption for Lead Plant (1, 25,000 TPA) including STP water

Name of Product		Process water consumption per unit of product output(cum/MT)	
		During the previous financial year	During the current financial year
		(1)	(2)
Lead Cathode/Ingot	With STP water	5.63	6.36
	Fresh Water (without STP water)	0.30	0.77

(2) Raw material consumption

Name of raw material	Name of products	Consumption of raw material per unit of output MT	
		During the previous financial year	During the current financial year
Lead concentrate	Lead Cathode/Ingot	1.88	1.87
Coal for lead smelter		0.15	0.11
Coke for lead smelter		0.21	0.22
Lead Silver Compound*		0.02	0.02
Battery/Lead scrap and secondary*		Not Used	Not Used
Lead dross and lead bearing waste		0.014	0.012
Lime Stone		0.14	0.09
Iron Ore		0.03	0.017

PART-C

Pollution discharged to environment/ unit of output
(Parameter as specified in the consent issued)

Pollutants	Quantity of pollutants discharged (mass/day)	Concentration of pollutants in discharges (mass/volume)	Percentage of variation from prescribed standards
a) Water	Not Applicable as Zero Discharge is maintained.		
pH			
TDS			
DO			
Suspended Solids			
Oil and Grease			
Chromium as hexavalent			
Manganese			
Nickel			
Copper			
Zinc			
Cadmium			
Lead			
Mercury			
Cyanide			
b) Air			
	Lead Plant		
Particulate matter	385.96 Kg/Day	35.14 mg/nm ³	- 29.70
SO ₂	412.52 Kg/Day	220.82 mg/nm ³	- 76.75
Acid Mist	57.60 Kg/Day	30.78 mg/nm ³	-38.43
Lead (Pb)	44.81 Kg/Day	4.12 mg/nm ³	- 58.72

** Total Particulate matter & Lead emission from 4 stacks (Primary-SKS, Secondary-BFF, Lead refinery Pyro plant North & South) of Lead Smelter.

PART-D
Hazardous Waste

As specified under Hazardous Wastes (Management, Handling & Transboundary Movement)
Rules, 2016

As DSC is having common Hazardous waste authorization, which includes Zinc, Lead and CPP, so mentioned hazardous waste generation is for complete DSC location.

Hazardous Waste	Total Quantity Generation (Kg.)	
	During the previous financial year	During the current financial Year
(a) From process		
- Jarosite	189786000	198872600
- Purification Cake	3921040	3607000
- Anode Mud	1132000	1057000
- Cooler Cake	2947270	2855740
- Cobalt Cake	---	
- Used /spent Oil	38620	50180
- Spent Catalyst (V2O5)	29440	26180
- Chemical Sludge (Salts)	1233900	2101940
- Discarded Containers/barrels/liners used for hazardous waste/Chemicals	148 Nos	131 no.
- Flue Gas Cleaning Residue	--	
- Spent ion exchange resin containing Toxic metal	--	1440
- Oil soaked filter	--	
- Waste/residues containing oil	2980	8820
- Process Residue	19947640	19983160
(b) From pollution control facilities		
- Non-ferrous sludge from ETP and scrubbers (ETP Cake)	14005430	14215340

PART-E

SOLID WASTE

DSC has a common storage facility for storage of Scrap, which includes Zinc, Lead and CPP, so mentioned waste generated is for completed DSC location.

Solid Waste	Total Quantity Generation (Kg.)	
	During the previous financial year	During the current financial Year
(a) From process		
<i>Metal Scrap</i>	753820	583490
<i>Wooden Scrap</i>	98388	84034
<i>Plastic Waste</i>	7640	9330

Solid Waste generation specific to lead plant

Solid Waste	Total Quantity Generation (Kg.)	
	During the previous financial year	During the current financial Year
(a) From process		
<i>Fuming Furnace Slag</i>	71169000	73262278

PART-F

Please specify the characterization (in terms of composition and quantum) of hazardous as well as solid wastes and indicate disposal practice adopted for both the categories of wastes.

Details of Solid Wastes & Its Disposal Method

Sr. No.	Name of waste	Quantity (MT)	Chemical Characteristics (%)	Mode of Treatment / Disposal
1	Jarosite	198872.6	Zn: 2.5 -5 Pb: 5-7 Fe: 25-31	Stabilization with lime & cement as Jarofix using patented Jarofix Technology (M/s Canadian Electrolytic Zinc), followed by disposal in Jarofix yard.
2	Non-ferrous sludge from ETP and scrubbers (ETP Cake)	14215.34	Zn: 1- 8 Cu: 0.01 – 0.02 Pb: 0.2 – 0.5	Disposal in captive SLF after stabilization.
3	Cooler Cake	2855.74	Zn: 0.5-1.5 Balance Gypsum	Disposal in captive SLF after stabilization.
4	Purification Cake	3607.0	Zn: 20 - 35 Cd: 8-10 Cu: 3-12	Sale to authorized recyclers registered with CPCB/ MoEF.
5	Anode Mud	1057.0	Mn: 30-45 Zn: 0.3 - 1 Pb: 5-8	Reuse/sale to authorized recyclers registered with CPCB/ MoEF and surplus disposal to captive SLF.
6	Used Oil/Spent Oil	50.18	--	Reuse/sale to authorized recyclers registered with CPCB/ MoEF.
7	Chemical Sludge (Salts)	2101.94	Sodium Salts (Na ₂ SO ₄ .10H ₂ O etc)	Disposal in SLF
8	Spent Catalyst (V ₂ O ₅)	26.18	V ₂ O ₅	Disposal in SLF
9	Discarded Containers/barrels/liners used for	131 Nos.	--	Disposal in SLF

	hazardous waste/Chemicals			
10	Cobalt Cake	--	--	No Generation
11	Flue Gas Cleaning Residue	--	--	No Generation
12	Spent ion exchange resin containing Toxic metal	--	--	No Generation
13	Oil soaked filter	--	--	Incineration in TSDF
14	Waste/residues containing oil	8.82	--	Sale to registered recycler
15	Process Residue	19983.16	--	Reuse/sale to authorized recyclers registered with CPCB/ MoEF.
16	Fly Ash	130303.91	116555.05	Provided to Cement Manufacturers
			13748.86	Backfilling in mines
17	Bottom Ash	35031.53	35031.53	Provided to Brick manufactures
18	Metal Scrap	583.490	--	Sent to recyclers
19	Wooden Scrap	84.034	--	Sent to recyclers
20	Plastic Waste	9.330	--	Sent to recyclers

Waste Generation specific to Lead Plant

Sr. No.	Name of waste	Quantity Generated (MT)	Quantity used	Disposal Method
16	<i>Fuming Furnace Slag</i>	73262.278	--	Provided to Cement Manufacturers

PART-G**Impact of the pollution abatement measures taken on conservation of natural resources and on the cost of production.**

Our aim is to preserve the long- term health of the natural environment affected by our operations. We set and achieve targets that promote efficient use of resources and include the reduction and prevention pollution.

Air Environment**Control of SO₂ Emissions in Acid Plant**

During operation of the smelter complex, the main emission sources are SO₂ from stack attached to Sulphuric Acid Plant. SO₂ emission is restricted to 1.5 kg/tone of acid and acid mist is controlled below 50 mg/Nm³ which conform to the stipulated regulatory norms. Adequate stack height (105-m.) has been provided. TGT Plant has been provided for scrubbing of SO₂ in tailing gas. SO₂ is scrubbed with the help of calcine into ZnSO₄.

Water Environment

We have a long-term approach to water management that aims to improve our performance, recognize the significance of water, and contribute to sustainable water management. We understand its importance and adopt best practices for making the judicious use of water and conserve it.

Effluent generated from the Dariba Smelter complex is treated in Effluent Treatment Plant (ETP) of capacity 9000 m³/day along with 8850 m³/day capacity of RO plant.

The effluents generated from gas cleaning plant, sulphuric acid plant, anode and cathode washing, DM plant, cooling towers and power plant are treated to neutralize the acidity and to precipitate and remove metallic elements.

Treated water is reused/ recycled in processes. Multiple Effect Evaporator (MEE) and Solar Evaporation Ponds have been provided to treat RO reject water to ensure Zero Effluent Discharge from the plant premises.

Sewage collected from the plant is collected in septic tanks followed by soak pits. Sewage collected from residential colony is treated in Sewage Treatment Plant (STP) established in the colony itself.

Storm water ponds of adequate capacity have been constructed inside the plant premises for storing the drain water for further treatment in the ETP. It is used in the monsoon in conserving the rainwater for further use in the plant.

Waste Management

We focus on a '4R' waste strategy - Reduce, Recycle, Reuse and Reclaim and 'Eco-friendly' disposal of process residues. The solid wastes generated from the Lead smelter are given in 'Part F' of the environmental statement.

Slag Yard with thick clay liner has been constructed in the plant premises for the proper disposal of the waste for preventing the deterioration of the land and water environment.

Noise

In the Smelter noise is generated from waste heat recovery boiler, fans, compressors and blowers. All equipments in the Smelter have been designed /operated to have a noise level in line with the regulatory requirements. Necessary acoustic enclosures have been provided to limit noise levels within the norms.

PART-H

Additional measures/investment proposal for environment protection including abatement of pollution /prevention of pollution.

Green belt Development

Implementation of afforestation program is of paramount importance for Dariba Smelter Complex. In the financial years 2009-2025, 269040 nos. of saplings have been planted successfully. Drip irrigation facility has been provided to all the plant saplings.

- Dust capturing efficiency;
- Plant's growth;
- Canopy cover; and
- Origin of plant
- Arid Climatic conditions

PART-I

Any other particular for improving the quality of the environment.

Environmental Monitoring

Regular monitoring of important and crucial environmental parameters is of immense importance to assess the status of environment during plants operation. With the knowledge of baseline conditions, the monitoring program can serve as an indicator for any deterioration in environmental conditions due to operation of the plants and suitable preventive steps could be taken in time to safeguard the environment. Monitoring is as important as that of control of pollution since the efficiency of control measures can only be determined by monitoring. A

full-fledged environmental laboratory has been set up for regular monitoring of environmental parameters, inside and outside the plant.

The environmental attributes being monitored are as given below:

- Air Pollution and Meteorological Aspects
- Water and Waste water Quality
- Noise Levels
- Soil Quality