



सी.पी.पी.,जावर माईत्स पिन कोड - 313901

HINDUSTAN ZINC LIMITED हिन्द्रस्तान जिंक लिभिटेड

CPP, Zawar Mines PIN Code - 313901

जिला - उदयपुर (गज्.)

Telephone - (0294) 2723400

Dist - Udaipur (Raj.)

Ref.: HZL/ZM/CPP/ENV/2025

Date -29.08.2025

## By Registered

The Member Secretary Rajasthan State Pollution Control Board 4- Institutional Area, Jhalana Dungri JAIPUR-302004 (Raj.)

Sub.: Environmental Statement for the year 2024-25 for Zawar CPP

Ref: F(Mines)/Udaipur(Sarada)/50(1)/2016-2017/2021-2023 dated

21.06.2023

Sir,

Please find attached herewith the Environmental Statement for the year 2024-25 for Zawar Captive Power Plant

Thanking you

Yours Faithfully

(Head - ZAWAR CPP)

Encl.: As above

CC: 1. The Deputy Director (S), Scientist- C, Ministry of Environment, Forest & Climate Change, Integrated Regional Office, B-213 & 216, Aranya Bhawan, Jhalana Institutional Area, Jaipur (Rajasthan)- 302004

2. The Regional Officer, Rajasthan State Pollution Control Board, F-470, Near UCCI Building, Madri Industrial Area, Udaipur-313003 (Raj.)

3. Office Copy Env. Cell/CPP Zawar

Star City

### FORM - V

## (See Rule- 14)

## Environmental Statement for the financial year ending the 31st March 2025

## PART - A

(i)	Name and Address of the Owner / Occupier of the Industry / Operation and Process	Sh. Arun Mishra (Occupier) CEO & Whole Time Director Hindustan Zinc Limited, Yashad Bhawan, Udaipur-313001 (Raj) Mohammad Parvez (Factory Manager) Head CPP ZAWAR Hindustan Zinc Limited, Zawar Mines Dist Udaipur- 313901 (Raj)
(ii)	Industry category	Red
(iii)	Production capacity	90 MW Power Generation
(iv)	Year of establishment	16.12.2008
(v)	Year of last environment statement submitted.	27.08.2024

#### PART - B

## Water and Raw Material Consumption

(i) Water consumption m³/day

Process- 4488.58 Cooling- NA Domestic- NA

Name of Product	S	Process water consum product output	ption per unit of					
		During the previous financial year (2023-24)	During the current financial year (2024-25)					
		(1)	(2)					
(1) Power		2.31 m <sup>3</sup> /MWh	2.23 m <sup>3</sup> /MWh					
(ii) Raw materia	l consumpti	on						
*Name of raw	Name of	• 0.00 0.0000	w material per unit of put*					
*Name of raw Name of materials Products		during the previous financial year (2023-24)	during the current financial year (2024-25)					
Coal Power		484.70	528.45					

<sup>\*</sup> gm/kwh

Increase in coal consumption is due to use of lower GCV coal (Higher consumption of Domestic Coal) and higher electricity generation as compared to previous year.

#### PART - C

Pollution discharged to environment/unit of output.

(Parameter as specified in the consent issued)

(1) Pollution	Quantity of pollutants discharged (m³/day)	Concentration of pollutants in discharges (m³/day)	Percentage of variation from prescribed standards with reasons
(a) Water	Zero Discharge	Within the limits as prescribed by RSPCB in Consent to Operate	NIL
(b) Air	Less than 50 mg/Nm³ of SPM	Within the limits as prescribed by RSPCB in Consent to Operate	NIL

## PART - D

#### **HAZARDOUS WASTES**

(as specified under Hazardous Wastes (Management, Handling & Transboundary Movement) Rules 2016)

	Total quantity dur	ing the year (MT)
Hazardous wastes	during the previous financial year	during the current financial year (2024-25)
(a) From Process		
Used/Spent Oil Sold	5.14	0.98
(b) From pollution control facility	Nil	Nil

Note: Used oil from entire location is collected and sold from central store of Zawar Mines. As Zawar Mines complex (including CPP) is having common HWs authorization, quantity of oil sold from central store has been mentioned in Environment statement submitted for Zawar mines that includes for entire location including CPP.

PART - E

#### **Solid Wastes**

		Total Qua	intity (MT)		
	y	evious financial ear 23-24)	during the current financi year (2024-25)		
<ul><li>(a) From process</li><li>(b) From Pollution control facility</li></ul>	Fly Ash	Bottom Ash	Fly Ash	Bottom Ash	
(c) (1) Quantity recycled or re- utilized within the unit.	-	601.93	-	126.52	
(2) Sold	50259.76	4818.20	81944.31	11185.23	
(3) Disposed	-		-	-	

#### PART - F

Please specify the characteristics (in terms of composition and quantum) of hazardous as well as solid wastes and indicate disposal practice for both of these categories of wastes.


- 1. The Hazardous Waste generated is used / spent oil which is stored in 220 litre drums and then disposed to registered/ authorized recyclers.
- 2. Solid wastes generated are Fly Ash and Bottom Ash. These are sold to Cement Plants/ brick manufacturers in suitably designed bulkers owned by the cement plants. Also, bottom ash is partially recycled.

#### PART - G

Impact of the pollution abetment measures taken on conservation of natural resources and on the cost of production

It may be noted that higher production of power is achieved taking following measures:

- > Better capacity utilization of plant and equipment;
- > Better maintenance practices resulting in lesser downtime and increased plant availability.
- 8 field ESP to arrest SPM going through chimney to maintain the emission below specified limit.
- Online monitoring system at stack for continuous monitoring of pollutants.
- Zero Discharge is followed. 100% blow down water reused for dust suppression as well for reuse in beneficiation plant
- STP water after treatment is pumped to blow down tank of CPP and utilized in CPP
- Cyclone separators and Bag filters at the transfer points so as to ensure minimum fugitive emission.
- Covered Coal conveyers for conveying of coal.
- Dust suppression and Dust extraction system installed to improve emissions within the plant premises.
- Regular care of the plantation is being taken.




8 Field ESP



Ash Transportation via Bulker



Covered conveyor belt



**Covered Conveyor Belt** 




Transportation via covered trucks




Concrete roads in Plant



Mist sprinkling system in coal yard



Water sprinkling system at coal yard




Coal Crusher Building



CAAQMS



Acoustic Enclosure for Turbine





Plantation Near Boiler Plant



**Plantation Near Crusher House** 



Plantation Near DM Plant



Plantation Near Switch Yard







Stack Mercury Monitoring Station

### PART - H

Additional measures/investment for environmental protection abatement of pollution, prevention of pollution.

- 1. Water spraying on approach roads, coal yard to minimize fugitive dust outside the plant.
- 2. Monitoring of ambient air quality on regular basis at four locations, monitoring of both the stacks as well as water sample analysis
- 3. Proper training given to employees on various environment aspects like waste management, water awareness, climate change management and environment rules and regulation etc.
- Zawar location including Captive Power Plant is certified for ISO-9001:2015(QMS), ISO-14001:2015 (EMS), ISO-45001:2018 (OHSMS) and SA-8000:2014 (Social Accountability)

Any other information for improving the quality of the environment.

1. World Environment day was celebrated on  $5^{th}$ June. Various competitions for employees and children were conducted. Prizes were given to the winners on spot.



# 2. Safety Day was celebrated in the CPP premises.



**3. Energy Conservation Week Celebration:** Celebrated energy conservation week in which various events like poster, slogan & crossword competition were organized. Conserve to preserve hour organized in office premises. Organized **No Vehicle Day** on 14<sup>th</sup> December.



		HINDUSTA	N ZINC LI	MITED	
	STACK M	ONITORING	(in mg/N	m3), CPP ZAWAR	
Stacks			ESP		Coal Crusher
Parameters	PM	SOx	Nox	Hg	PM
Limits	50	-	-	0.03	50
Apr-24	26.5	819.2	225.5	0.0090 (Online data)	27.3
May-24	28.9	861.7	255.5	0.0097 (Online data)	28.5
Jun-24	27.2	826.3	219.7	0.0103 (Online data) (Average Value)	27.4
Jul-24	27.7	796.3	229.9	0.0109 (Online data) (Average Value)	25.5
Aug-24	29.7	855.2	275.1	0.0115 (Online data) (Average Value)	27
Sep-24	28	770.6	253.8	0.0128 (Online data) (Average Value)	27.4
Oct-24	29.3	867.1	282.9	0.0143 (online data) (Average Value)	28.3
Nov-24	29.4	829	229.7	0.016 (Online data) (Average Value)	26.9
Dec-24	26.6	788.2	263.5	0.019 (Online data) (Average Value)	27.2
Jan-25	27	810.3	229.6	0.020 (Online data) (Average Value)	26.6
Feb-25	29.4	855.5	263.7	0.0204 (Online data) (Average Value)	27.8
Mar-25 25		828.2	235	0.0199 (Online data) (Average Value)	29

# Ambient Air average values (in µg/m3) for 2024-25

Location	Parameters	Limits	Apr- 24	May- 24	Jun- 24	Jul-24	Aug- 24	Sep- 24	Oct- 24	Nov- 24	Dec- 24	Jan- 25	Feb- 25	Mar- 25
	PM 10	100	56.25	56.4	48.6	46	51.35	52.75	56.8	53.8	56.5	57.65	57.45	56
	PM 2.5	60	33.4	33.8	29	25.6	30.6	31.65	34	32.15	33.6	34.5	34.15	34.1
Ashok Nagar	SOx	80	6.75	7	6.35	6.2	6.2	6.35	6.7	6.4	6.65	6.7	7.05	6.45
	NOx	80	11.45	10.85	8.7	8.6	9.25	9.2	10.05	9.5	9.85	9.95	10.65	8.9
	со	4000	687.5	744.5	573	458	630	630	744.5	744.5	744.5	744.5	859	687
	PM 10	100	60.2	60.15	62.05	57.4	57.25	59.35	60.5	59.5	64.35	59.4	63.45	59.75
	PM 2.5	60	36.05	36.5	36.85	34.3	34	36.15	35.6	35.6	38.4	35.1	38.65	35.4
Weigh Bridge	SOx	80	7.7	7.6	7.7	7.5	6.5	7	7.25	6.9	7.35	7.35	7.7	7.35
	NOx	80	13.6	12.5	12.6	11.8	10.15	10.95	10.9	10.85	11.25	10.5	12.25	10.7
	СО	4000	744.5	859	801.5	687	744.5	744.5	859	744.5	859	859	859	744.5
	PM 10	100	60.4	63.7	61.45	60.1	60.15	63.45	62.8	63.05	68.5	65.6	65.75	69.5
	PM 2.5	60	36.25	39.15	37.2	35.7	36.25	37.5	37.3	37.6	40.75	39.15	40.15	41.45
Main Gate	SOx	80	8	8.6	8.05	8.1	6.7	7.2	7.7	7.35	8	8.05	8.15	8.4
	NOx	80	15.9	15.85	14.55	14.5	11.05	12.75	12.25	13	13.15	12.95	12.9	12.15
	со	4000	859	973.5	859	802	744.5	859	973.5	859	973.5	1030. 5	1031	1145
	PM 10	100	59.1	60.85	56.35	53.6	53.45	56.1	60.8	57	61.55	61.05	66.15	61.9
	PM 2.5	60	35.3	37.2	33.8	32	32.25	33.7	36.3	34.25	36.35	36.4	39.85	36.75
MAS Office	SOx	80	7.45	7.9	7.3	6.9	6.6	6.7	7.2	6.85	7.1	7.2	8	7.5
	NOx	80	12.85	13.05	10.95	9.2	10.75	11.35	12.3	11.45	10.65	11.15	12.75	11.25
	со	4000	687.5	859	630	573	744.5	744.5	801.5	801.5	859	630	859	744.5

# Day time Noise Levels [in dB(A)] for 2024-25

Location	Apr-24	May-24	Jun-24	Jul-24	Aug-24	Sep-24	Oct-24	Nov-24	Dec-24	Jan- 25	Feb-25	Mar- 25
Near Main Gate	62.5	64.1	62.9	60.1	58.8	58.6	57.9	62.7	61.5	57	57.6	58.1
Near STP	59.3	64.5	66.1	63.4	63.1	62.8	64.3	59.2	65	62.2	63.5	64.2
Near Weigh Bridge	62	60.9	58.7	65	64.8	64.3	65.1	66.9	62	64.8	63.7	63.6
Mass Office	66.7	63	59.6	64.2	64.6	63.9	63.5	65.3	64.7	64.4	61.8	62.8
Permissible Limit						7	5					<u>'</u>

# Night time Noise Levels [in dB(A)] for 2024-25

Location	Apr-24	May-24	Jun-24	Jul-24	Aug-24	Sep-24	Oct-24	Nov-24	Dec-24	Jan- 25	Feb- 25	Mar- 25
Near Main Gate	54.6	50.5	52.4	50.7	50.1	52.2	50.5	55	50.7	48.9	50.1	48.5
Near STP	57.9	59.8	63.4	62	61.5	60.4	61	57.8	62.3	60.5	59.8	60.6
Near Weigh Bridge	58.4	55.4	53.1	52.4	54	55.1	57.5	58.4	52.5	54.3	53.5	53
Mass Office	56.2	52.7	50.4	53.5	54.5	56.7	54.9	57	58.2	55.3	56	55.9
Permissible Limit			•	•		7	0					

# **Final Treated Water Analysis Report for 2024-25**

Parameters	Limits	Apr- 24	May- 24	Jun-24	Jul-24	Aug- 24	Sep-24	Oct- 24	Nov- 24	Dec-24	Jan- 25	Feb- 25	Mar- 25
TSS mg/lt	100	<5	<5	<5	14	8	15	10	10	8	6	13	8
BOD mg/lt	30	<2	<2	<0.2	8	5	9	7	5	4	4	8	9
COD mg/lt	250	<5	<5	<0.8	40	30	48	40	32	15	15	39	44
pН	6.5-8.5	7.60	7.63	7.80	7.38	7.19	7.62	7.82	7.48	7.44	7.55	7.14	7.56
Phosphate as P mg/lt	5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5
Oil & Grease mg/lt	10	<5	<5	< 5	<5	<5	<5	<5	<5	<5	<5	<5	<5
Free Available Chlorine mg/lt	0.5	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2	< 0.2
Copper mg/lt	1	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Iron mg/lt	1	0.10	0.12	0.10	0.03	0.03	0.06	0.04	0.04	0.03	0.03	0.05	0.04
Total Chromium Cr+6 mg/lt	0.2	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Zinc mg/lt	1	0.15	0.18	0.15	0.08	0.06	0.20	0.11	0.10	0.03	0.04	0.02	0.03
Sulphide mg/lt	2	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	<0.5	< 0.5	<0.5	<0.5	<0.5
Temperture °C	Not more than 10°C higher than the intake water temperature	33.1	39.4	35.2	29.5	28.4	30.4	32	25.5	17.3	20	26	34

# Ashok Nagar STP Analysis Report for 2024-25

Except pH all value are in mg/lt

Parameters	Limits As per CTO	Apr-24	May-24	Jun-24	Jul-24	Aug-24	Sep-24	Oct-24	Nov-24	Dec-24	Jan- 25	Feb- 25	Mar- 25
Total Suspended Solids	100	11	8	6	8	7	8	7	6	6	15	14	<5
pH Value	5.5- 9.0	7.29	7.40	7.23	7.40	7.34	7.15	7.40	7.40	7.22	7.55	7.60	7.57
Oil and Grease	10	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5
Total Residual Chlorine	1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1
Ammonical Nitrogen (as N)	50	5.2	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5	<5
Total Kjeldahl Nitrogen (as N)	100	6.7	6.3	5.8	6.1	5.6	5.2	5	<5	5.7	<5	<5	<5
Biochemical Oxygen Demand (3 days at	30	10	9	7	6	8	9	8	7	8	7	8	9
27°C) Sulphide (as S)	2	<0.5	<.5	<.5	<0.5	<.5	<.5	<0.5	<0.5	<0.5	<0.5	<.5	<.5
Nitrate Nitrogen	10	3.3	3.6	4.2	4,4	4.2	4.8	4	5.7	4.2	4.6	4.24	7.34
Chlorides	1000	113.9	119.9	149.9	99.9	125.9	119.9	99.9	139.9	125.9	139.9	125.9	133.9
Sulphates	1000	340.5	296.4	210.5	192.7	263.5	189.6	210.2	210.2	167.4	210.2	356.4	192.6
Chemical Oxygen Demand	250	88	45	40	30	40	47	40	40	43	40	47	40

# **Total Expenses for 2024-25**

Particulars	Amount in Rs.
Plantation/Monitoring/Ash/RSPCB/Other Env Exp	18,73,845.30